

STRUCTURAL CALCULATIONS


Vaney Shinde Residence
4207 W Mercer Way,
Mercer Island, WA 98040

Studio Ectypos
4212 W Mercer Way,
Mercer Island, WA 98040

June 24, 2020

**Supplemental
Calculations – Intake
comments**





○ Key - Footing load cases

Vaney Shinde - Footing Loads & Tribs

Foundations are structurally acceptable for the loading below, including 5 psf wet snow surcharge.

Load Map	DL (psf)	LL (psf)	SL (psf)*
Roof, typ	15		30
Floors, typ	15	40	
Decks	15	60	

* Includes 5 psf surcharge for low slope roof

Case	Trib (ft)	Walls DL (plf)	Net loads			D+L (plf)	D+S (plf)	D+0.75(L+S) (plf)	
			DL (plf)	LL (plf)	SL (plf)				
Case 1	Roof	11.5	141	314		345			
	Upper	11.5	134	306	460				
	Main	11.5		173	460				
	Σ			792	920	345	1712	1137	1741
	Case 2	Roof	8.0	141	261		240		
Upper		9.5	134	276	380				
Main		9.5	146	289	380				
Σ				826	760	240	1586	1066	1576
Case 3		Roof	12.0	141	321		360		
	Upper	7.5	134	246	300				
	Main	0.7		10	27				
	Σ			577	327	360	904	937	1092
	Case 4	Roof	7.5	141	254		225		
Upper		0.7	134	144	27				
Main		0.7		10	27				
Σ				407	53	225	460	632	616
Case 5		Roof	12.0	141	321		360		
	Upper	1.3	134	154	80				
	Main	1.3	60	80	80				
	Σ			555	160	360	715	915	945
	Case 6	Roof	2.0	141	171		60		
Upper		0.7	134	144	40				
Main		4.5	60	128	270				
Σ				442	310	60	752	502	720
Case 7		Roof	4.0	141	201		120		
	Upper	4.0	134	194	160				
	Main	4.0		60	160				
	Σ			455	320	120	775	575	785

Vaney Shinde - Footing Loads & Tribs

Case 8	Trib (ft)	Walls	Net loads			D+L (plf)	D+S (plf)	D+0.75(L+S) (plf)
		DL (plf)	DL (plf)	LL (plf)	SL (plf)			
Roof			0		0			
Upper	12.0	134	314	720				
Main		1219	1219	0				
Σ			1532	720	0	2252	1532	2072
Case 9	Trib (ft)	Walls	Net loads			D+L (plf)	D+S (plf)	D+0.75(L+S) (plf)
		DL (plf)	DL (plf)	LL (plf)	SL (plf)			
Roof	2.0	141	171		60			
Upper	10.0	134	284	400				
Main	14.5	60	278	670				
Σ			732	1070	60	1802	792	1580



Company:		Date:	6/22/2020
Engineer:		Page:	1/5
Project:			
Address:			
Phone:			
E-mail:			

1. Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General

Design method: ACI 318-14
Units: Imperial units

Anchor Information:

Anchor type: Cast-in-place
Material: AB
Diameter (inch): 0.875
Effective Embedment depth, h_{ef} (inch): 12.000
Anchor category: -
Anchor ductility: Yes
 h_{min} (inch): 14.38
 C_{min} (inch): 5.25
 S_{min} (inch): 5.25

Base Material

Concrete: Normal-weight
Concrete thickness, h (inch): 15.00
State: Cracked
Compressive strength, f_c (psi): 2500
 $\Psi_{c,v}$: 1.0
Reinforcement condition: A tension, A shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: Yes
Ignore concrete breakout in tension: No
Ignore concrete breakout in shear: No
Ignore 6do requirement: No
Build-up grout pad: No

Recommended Anchor

Anchor Name: PAB Pre-Assembled Anchor Bolt - PAB7 (7/8"Ø)





Company:		Date:	6/22/2020
Engineer:		Page:	2/5
Project:			
Address:			
Phone:			
E-mail:			


Load and Geometry

Load factor source: ACI 318 Section 5.3
Load combination: not set
Seismic design: Yes
Anchors subjected to sustained tension: Not applicable
Ductility section for tension: 17.2.3.4.3 (c) is satisfied
Ductility section for shear: 17.2.3.5.2 not applicable
 Ω_0 factor: not set
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: Yes

Strength level loads:

N_{ua} [lb]: 8500
 V_{uax} [lb]: 0
 V_{uay} [lb]: 0

<Figure 1>




Input data and results must be checked for agreement with the existing circumstances, the standards and guidelines must be checked for plausibility.



Company:		Date:	6/22/2020
Engineer:		Page:	3/5
Project:			
Address:			
Phone:			
E-mail:			

<Figure 2>





Company:		Date:	6/22/2020
Engineer:		Page:	4/5
Project:			
Address:			
Phone:			
E-mail:			

3. Resulting Anchor Forces

Anchor	Tension load, N _{ua} (lb)	Shear load x, V _{uax} (lb)	Shear load y, V _{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2 + (V_{uay})^2}$ (lb)
1	8500.0	0.0	0.0	0.0
Sum	8500.0	0.0	0.0	0.0

Maximum concrete compression strain (%): 0.00
 Maximum concrete compression stress (psi): 0
 Resultant tension force (lb): 8500
 Resultant compression force (lb): 0
 Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
 Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00

4. Steel Strength of Anchor in Tension (Sec. 17.4.1)

N _{sa} (lb)	φ	φN _{sa} (lb)
26795	0.75	20096

5. Concrete Breakout Strength of Anchor in Tension (Sec. 17.4.2)

$$N_b = 16\lambda_a \sqrt{f_c} h_{ef}^{5/3} \text{ (Eq. 17.4.2.2b)}$$

λ _a	f _c (psi)	h _{ef} (in)	N _b (lb)
1.00	2500	12.000	50318

$$0.75\phi N_{cb} = 0.75\phi (A_{Nc} / A_{Nco}) \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b \text{ (Sec. 17.3.1 \& Eq. 17.4.2.1a)}$$

A _{Nc} (in ²)	A _{Nco} (in ²)	c _{a,min} (in)	Ψ _{ed,N}	Ψ _{c,N}	Ψ _{cp,N}	N _b (lb)	φ	0.75φN _{cb} (lb)
768.75	1296.00	10.00	0.867	1.00	1.000	50318	0.75	14551

6. Pullout Strength of Anchor in Tension (Sec. 17.4.3)

$$0.75\phi N_{pn} = 0.75\phi \Psi_{c,P} N_p = 0.75\phi \Psi_{c,P} 8A_{brg} f_c \text{ (Sec. 17.3.1, Eq. 17.4.3.1 \& 17.4.3.4)}$$

Ψ _{c,P}	A _{brg} (in ²)	f _c (psi)	φ	0.75φN _{pn} (lb)
1.0	4.07	2500	0.70	42683



Company:		Date:	6/22/2020
Engineer:		Page:	5/5
Project:			
Address:			
Phone:			
E-mail:			

11. Results

11. Interaction of Tensile and Shear Forces (Sec. D.7)?

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	8500	20096	0.42	Pass
Concrete breakout	8500	14551	0.58	Pass (Governs)
Pullout	8500	42683	0.20	Pass

PAB7 (7/8"Ø) with hef = 12.000 inch meets the selected design criteria.

12. Warnings

- Per designer input, ductility requirements for tension have been determined to be satisfied – designer to verify.
- Per designer input, the shear component of the strength-level earthquake force applied to anchors does not exceed 20 percent of the total factored anchor shear force associated with the same load combination. Therefore the ductility requirements of ACI 318 17.2.3.5.2 for shear need not be satisfied – designer to verify.
- Designer must exercise own judgement to determine if this design is suitable.



Company:		Date:	6/22/2020
Engineer:		Page:	1/5
Project:			
Address:			
Phone:			
E-mail:			

1. Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General

Design method: ACI 318-14
Units: Imperial units

Anchor Information:

Anchor type: Cast-in-place
Material: AB
Diameter (inch): 1.000
Effective Embedment depth, h_{ef} (inch): 12.000
Anchor category: -
Anchor ductility: Yes
 h_{min} (inch): 14.63
 C_{min} (inch): 6.00
 S_{min} (inch): 6.00

Base Material

Concrete: Normal-weight
Concrete thickness, h (inch): 15.00
State: Cracked
Compressive strength, f_c (psi): 2500
 $\Psi_{c,v}$: 1.0
Reinforcement condition: A tension, A shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: Yes
Ignore concrete breakout in tension: No
Ignore concrete breakout in shear: No
Ignore 6do requirement: No
Build-up grout pad: No

Recommended Anchor

Anchor Name: PAB Pre-Assembled Anchor Bolt - PAB8 (1"Ø)





Company:		Date:	6/22/2020
Engineer:		Page:	2/5
Project:			
Address:			
Phone:			
E-mail:			


Load and Geometry

Load factor source: ACI 318 Section 5.3
Load combination: $U = 0.9D + 1.0E$
Seismic design: Yes
Anchors subjected to sustained tension: Not applicable
Ductility section for tension: 17.2.3.4.3 (c) is satisfied
Ductility section for shear: 17.2.3.5.2 not applicable
 Ω_0 factor: not set
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: Yes

Service level loads:

	D	E	Strength level loads
N_a [lb]:	-506	12000	11545
V_{ax} [lb]:	0	0	0
V_{ay} [lb]:	0	0	0

<Figure 1>




Input data and results must be checked for agreement with the existing circumstances, the standards and guidelines must be checked for plausibility.



Company:		Date:	6/22/2020
Engineer:		Page:	3/5
Project:			
Address:			
Phone:			
E-mail:			

<Figure 2>





Company:		Date:	6/22/2020
Engineer:		Page:	4/5
Project:			
Address:			
Phone:			
E-mail:			

3. Resulting Anchor Forces

Anchor	Tension load, N _{ua} (lb)	Shear load x, V _{uax} (lb)	Shear load y, V _{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2 + (V_{uay})^2}$ (lb)
1	11545.0	0.0	0.0	0.0
Sum	11545.0	0.0	0.0	0.0

Maximum concrete compression strain (%): 0.00
 Maximum concrete compression stress (psi): 0
 Resultant tension force (lb): 11545
 Resultant compression force (lb): 0
 Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
 Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00

4. Steel Strength of Anchor in Tension (Sec. 17.4.1)

N _{sa} (lb)	φ	φN _{sa} (lb)
35150	0.75	26363

5. Concrete Breakout Strength of Anchor in Tension (Sec. 17.4.2)

$$N_b = 16\lambda_a \sqrt{f_c} h_{ef}^{5/3} \text{ (Eq. 17.4.2.2b)}$$

λ _a	f _c (psi)	h _{ef} (in)	N _b (lb)
1.00	2500	8.000	25600

$$0.75\phi N_{cb} = 0.75\phi (A_{Nc} / A_{Nco}) \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b \text{ (Sec. 17.3.1 \& Eq. 17.4.2.1a)}$$

A _{Nc} (in ²)	A _{Nco} (in ²)	c _{a,min} (in)	Ψ _{ed,N}	Ψ _{c,N}	Ψ _{cp,N}	N _b (lb)	φ	0.75φN _{cb} (lb)
507.50	576.00	10.00	0.950	1.00	1.000	25600	0.75	12053

6. Pullout Strength of Anchor in Tension (Sec. 17.4.3)

$$0.75\phi N_{pn} = 0.75\phi \Psi_{c,P} N_p = 0.75\phi \Psi_{c,P} 8A_{brg} f_c \text{ (Sec. 17.3.1, Eq. 17.4.3.1 \& 17.4.3.4)}$$

Ψ _{c,P}	A _{brg} (in ²)	f _c (psi)	φ	0.75φN _{pn} (lb)
1.0	5.15	2500	0.70	54117

Input data and results must be checked for agreement with the existing circumstances, the standards and guidelines must be checked for plausibility.



Company:		Date:	6/22/2020
Engineer:		Page:	5/5
Project:			
Address:			
Phone:			
E-mail:			

11. Results

11. Interaction of Tensile and Shear Forces (Sec. D.7)?

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	11545	26363	0.44	Pass
Concrete breakout	11545	12053	0.96	Pass (Governs)
Pullout	11545	54117	0.21	Pass

PAB8 (1"Ø) with hef = 12.000 inch meets the selected design criteria.

12. Warnings

- Per designer input, ductility requirements for tension have been determined to be satisfied – designer to verify.
- Per designer input, the shear component of the strength-level earthquake force applied to anchors does not exceed 20 percent of the total factored anchor shear force associated with the same load combination. Therefore the ductility requirements of ACI 318 17.2.3.5.2 for shear need not be satisfied – designer to verify.
- Designer must exercise own judgement to determine if this design is suitable.