The Washington State Energy Code requirements for alterations are located in Chapter 5 Alterations (remodels) do not need to obtain energy credits from Table R406.2  Additions must meet the requirements for new construction. This includes nonconditioned space being altered to become conditioned space.  Will the wall cavities be exposed?  If yes: Exposed wall cavities must be insulated -  2 X 4 wall studs require R-15 insulation  2 X 6 wall studs require R-21 insulation  Will the roof/ceiling framing cavities or attic be exposed?  If yes: Exposed roof/ceiling assemblies must be insulated -  Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  If yes: No	Alterations Worksheet 2015 Washington	on State End	ergy Code			
The Washington State Energy Code requirements for alterations are located in Chapter 5 Alterations (remodels) do not need to obtain energy credits from Table R406.2  Additions must meet the requirements for new construction. This includes nonconditioned space being altered to become conditioned space.  Will the wall cavities be exposed?  If yes: Exposed wall cavities must be insulated -  2 X 4 wall studs require R-15 insulation  2 X 6 wall studs require R-21 insulation  Will the roof/ceiling framing cavities or attic be exposed?  If yes: Exposed roof/ceiling assemblies must be insulated -  Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?  Yes  No  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  Yes	Project Information		Contact Informa	tion		
The Washington State Energy Code requirements for alterations are located in Chapter 5 Alterations (remodels) do not need to obtain energy credits from Table R406.2  Additions must meet the requirements for new construction. This includes nonconditioned space being altered to become conditioned space.  Will the wall cavities be exposed?  If yes: Exposed wall cavities must be insulated -  2 X 4 wall studs require R-15 insulation  2 X 6 wall studs require R-21 insulation  Will the roof/ceiling framing cavities or attic be exposed?  If yes: Exposed roof/ceiling assemblies must be insulated -  Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?  Yes  No  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  Yes	ARIHILO NAKAMURA					
Alterations (remodels) do not need to obtain energy credits from Table R406.2  Additions must meet the requirements for new construction. This includes nonconditioned space being altered to become conditioned space.  Will the wall cavities be exposed?  Yes No  If yes: Exposed wall cavities must be insulated - 2 X 4 wall studs require R-15 insulation 2 X 6 wall studs require R-21 insulation  Will the roof/ceiling framing cavities or attic be exposed?  Yes No  If yes: Exposed roof/ceiling assemblies must be insulated - Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?  Yes No  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  Yes No	MERCHRISLAND WA 980	40				
Alterations (remodels) do not need to obtain energy credits from Table R406.2  Additions must meet the requirements for new construction. This includes nonconditioned space being altered to become conditioned space.  Will the wall cavities be exposed?  Yes No  If yes: Exposed wall cavities must be insulated - 2 X 4 wall studs require R-15 insulation 2 X 6 wall studs require R-21 insulation  Will the roof/ceiling framing cavities or attic be exposed?  Yes No  If yes: Exposed roof/ceiling assemblies must be insulated - Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?  Yes No  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  Yes No	The second of the					
Will the wall cavities be exposed?  If yes: Exposed wall cavities insulated - 2 X 4 wall studs require R-15 insulation 2 X 6 wall studs require R-21 insulation Will the roof/ceiling framing cavities or attic be exposed?  If yes: Exposed roof/ceiling assemblies must be insulated - Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  Yes  No	The Washington State Energy Code require Alterations (remodels) do not need to o	rements for a btain energy	literations are / credits from	located in Chap Table R406.2	oter 5	
If yes: Exposed wall cavities must be insulated -  2 X 4 wall studs require R-15 insulation  2 X 6 wall studs require R-21 insulation  Will the roof/ceiling framing cavities or attic be exposed?  If yes: Exposed roof/ceiling assemblies must be insulated -  Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  Yes  No	Additions must meet the requirements for altered to become conditioned space.	/ (	CARAGE A	4000TON	ioned space being	
2 X 4 wall studs require R-15 insulation 2 X 6 wall studs require R-21 insulation  Will the roof/ceiling framing cavities or attic be exposed?  Yes  No  If yes: Exposed roof/ceiling assemblies must be insulated - Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?  No  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  Yes  No	Will the wall cavities be exposed? $($					
Will the roof/ceiling framing cavities or attic be exposed?  If yes: Exposed roof/ceiling assemblies must be insulated - Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  Yes  No	If yes: Exposed wall cavities n	nust be insula	ated -			
Will the roof/ceiling framing cavities or attic be exposed?  If yes: Exposed roof/ceiling assemblies must be insulated - Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  If yes: Insulated to R-30						
If yes: Exposed roof/ceiling assemblies must be insulated - Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?	2 X 6 wall stu	ds require R-	•21 insulation			
Vaulted ceilings: Insulate to the full depth of the framing member while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?   Yes  No  Are the windows and/or doors being replaced?  Yes  No	Will the roof/ceiling framing cavities or	attic be exp	osed?	□ Yes	□No	
while allowing for the minimum 1" ventilated space  Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?	If yes: Exposed roof/ceiling as	semblies mu	st be insulate	d -		
Flat ceilings: Install R-49 insulation or what the attic space can accommodate based on the roof pitch  Will the floor framing cavities be exposed?						
accommodate based on the roof pitch  Will the floor framing cavities be exposed?  If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?  Yes  No		while a	llowing for the	minimum 1" ve	ntilated space	
If yes: Exposed floor cavities must be insulated to R-30  Are the windows and/or doors being replaced?	Flat ceilings:		HANDER STRUMENT (1) 10 10 10 10 10 10 10 10 10 10 10 10 10			
Are the windows and/or doors being replaced? □ Yes □ No	Will the floor framing cavities be expose	ed?	□ Yes	□No		
14 보고 보고 있는데 보고 되었다면 보고 있는데 보	<b>If yes:</b> Exposed floor cavities n	must be insul	ated to R-30			
(includes both window of door and fightes)	Are the windows and/or doors being rep (includes both window or door and frame		□ Yes	□ No		
If yes: New windows and doors must have an area weighted average U-factor of ≤0.30		생김	an area weigh	ited average U-	factor of ≤0.30	
Will the heating or cooling system be replaced? □ Yes □ No	Will the heating or cooling system be replace		□ Yes	□No		
If yes: New equipment must meet current requirements and ducts need to be tested						
Will the hot water system be altered? ☐ Yes ☐ No	Will the hot water system be altered?	□ Yes	Е	No		
If yes: New water heating equipment must meet current code requirements	If yes: New water hea	ating equipm	ent must mee	t current code re	equirements	
Are more than 50% of the light fixtures being changed? ☐ Yes ☐ No	Are more than 50% of the light fixtures b	eing change	ed?	Yes	□No	
If yes: 75% of all lamps must be high efficacy (LED or CFL)			igh efficacy			