

Table with columns: CODE, REQUIRED? (Y/N), MATERIAL / ACTIVITY, EXTENT. Includes sections for LOADINGS, WIND CRITERIA, SEISMIC CRITERIA, STRUCTURAL DESCRIPTIONS, GENERAL CONDITIONS, FOUNDATION, DIMENSIONAL LUMBER, ANCHOR BOLT AND NAILING SPECIFICATIONS, and CONCRETE AND REINFORCING.

Table with columns: REQUIRED? (Y/N), MATERIAL / ACTIVITY, EXTENT. Contains technical specifications for concrete and reinforcing steel, including mix designs and curing requirements.

Table with columns: REQUIRED? (Y/N), MATERIAL / ACTIVITY, EXTENT. Contains technical specifications for masonry and wood construction, including inspection tasks and material requirements.

Table with columns: REQUIRED? (Y/N), MATERIAL / ACTIVITY, EXTENT. Contains technical specifications for soil, foundations, and special inspections for wind and seismic resistance.

Table with columns: SHEET NUMBER, SHEET NAME, ISSUE DATE. Contains a drawing list with 5 sheets including general notes, foundation plan, floor framing plan, roof framing plan, and framing details.



2906 74TH AVE SE REMODEL

2906 74TH AVE SE, MERCER ISLAND, WA 98040

DRAWING INFO

ISSUE DATE 07-25-22

ISSUED FOR PERMIT


PROJECT NO. 20242

ENGINEER BB

REVISION SCHEDULE

Table with 3 columns: NO., DATE, DESCRIPTION. Contains one revision entry.

GENERAL NOTES AND SPECIFICATIONS S-0



**2906 74TH AVE SE REMODEL**

2906 74TH AVE SE,  
MERCER ISLAND, WA  
98040

**DRAWING INFO**

ISSUE DATE 07-25-22

ISSUED FOR PERMIT


PROJECT NO. 20242

ENGINEER BB

**REVISION SCHEDULE**

NO.	DATE	DESCRIPTION

**BASEMENT/  
FOUNDATION  
PLAN  
S-1**



**IMPORTANT NOTES ON FIELD VERIFICATIONS AND TEMPORARY SHORING:**

1. CONTRACTOR SHALL REVIEW STRUCTURAL DRAWINGS AND FIELD VERIFY ALL RELATED EXISTING FRAMING & DIMENSIONS PRIOR TO ANY FIELD WORK. NOTIFY THE ENGINEER/OWNER ANY DISCREPANCIES FOUND IN THE FIELD. STRUCTURAL DRAWINGS MAY NOT CORRECTLY REFLECT ALL EXISTING FRAMING DUE TO LIMITED ACCESS TO THE SITE AND EXISTING DRAWINGS.
2. CONTRACTOR SHALL FIELD VERIFY AND NOTIFY THE ENGINEER/OWNER OF EXISTING MECHANICAL DUCTS, PLUMBING PIPES, ELECTRICAL WIRES THAT MAY INTERFERE WITH STRUCTURAL WORKS FOR COST CONSIDERATIONS PRIOR TO ANY FIELD WORK.
3. CONTRACTOR IS SOLELY RESPONSIBLE IN PROVIDING PROPER TEMPORARY SHORING PRIOR TO REMOVING ANY STRUCTURAL ELEMENTS. PLEASE CALL ENGINEER FOR QUESTIONS

**IMPORTANT NOTES ON FOUNDATION AND FRAMING:**

1. ALL FOOTINGS SHALL BEAR ON SUITABLE SOIL SUCH AS MIN. OF MEDIUM DENSE NATIVE SOIL OR COMPACTED STRUCTURAL FILL (NO SOFT OR ORGANIC MATERIALS). GEOTECHNICAL ENGINEER MAY BE REQUIRED TO ASSESS EXISTING SOIL CONDITIONS.
2. FOR FRAMING LUMBER TYPES AND GRADES, AND CONCRETE MIX REQUIREMENTS PLEASE SEE S-0
3. FOR PLYWOOD/OSB SHEARWALL SCHEDULE, PLEASE SEE S-4
4. FOR COMMON HEADER FRAMING DETAIL AND HEADER SIZE, SEE S-4
5. PROVIDE (2) 2X6 OR (3) 2X4 STUD POSTS AT EACH END OF BEAMS, UNLESS NOTED OTHERWISE ON PLAN
6. SLAB ON GRADE SHALL BE MIN. 4" THICK WITH #3 AT 18" EACH WAY (AT MID-DEPTH) ON 6" COMPACTED CRUSHED ROCK. PROVIDE 1" SAWCUT JOINT AT 15 FT MAX. SPACING (EACH WAY)
7. FLOOR SHEATHING SHALL BE 3/4" PLYWOOD OR OSB WITH 10d AT 6" NAILING AT EDGES AND AT 12" AT FIELD
8. ROOF SHEATHING SHALL BE 1/2" PLYWOOD OR OSB WITH 8d AT 6" NAILING AT EDGES AND AT 8" AT FIELD

**IMPORTANT NOTES ON TRUSS AND FLOOR FRAMING DESIGN/SHOP DRAWINGS:**

1. TRUSS FRAMING LAYOUT SHOWN IS GENERAL CONCEPT ONLY. CONTRACTOR/TRUSS SUPPLIER MUST SUBMIT TRUSS SHOP DRAWINGS INCLUDING TRUSS TEMPORARY/PERMANENT BRACING PLANS FOR ENGINEER'S REVIEW
2. TRUSS FRAMING PROFILE/LAYOUT SHOULD CONFORM TO BOTH STRUCTURAL AND ARCHITECTURAL DRAWINGS. ANY DEVIATIONS SHALL BE APPROVED BY ENGINEER/ARCHITECT PRIOR TO TRUSS DESIGN WORK.
3. TRUSS DEFLECTION CRITERIA:  
FLOOR/DECK TOTAL LOAD = L/480      ROOF TOTAL LOAD = L/240  
FLOOR/DECK LIVE LOAD = L/600      ROOF SNOW LOAD = L/300  
\*\* MAXIMUM TOTAL LOAD DEFLECTION SHOULD NOT EXCEED 1.0" IN ALL CASES
4. FLOOR/ROOF FRAMING LAYOUT AND CONNECTORS (SUCH AS LUMBER PACKAGE BY SUPPLIERS) MUST BE SUBMITTED FOR ENGINEER'S REVIEW PRIOR TO CONSTRUCTION

**FRAMING SYMBOLS:**

	SIMPSON WSW STRONG WALL (24" WIDE)		CONTINUOUS POST
	PLYWOOD SHEARWALL		POST STOPS BELOW THIS FLOOR
	SHEARWALL HOLDOWN		POST STARTS AT THIS FLOOR

**LEGEND AND NOTES**  
1/4" = 1'-0"

**1** BASEMENT/FOUNDATION PLAN  
1/4" = 1'-0"

**PORCH NOTE:**  
WORK ASSOCIATED WITH EXISTING NON-CONFORMING PORCH ARE FOR STRUCTURAL STABILITY AND MAINTENANCE ONLY. PORCH SHALL NOT BE EXPANDED IN SIZE



**2906 74TH AVE SE REMODEL**


2906 74TH AVE SE,  
MERCER ISLAND, WA  
98040

**DRAWING INFO**

ISSUE DATE	07-25-22
ISSUED FOR	PERMIT
PROJECT NO.	20242
ENGINEER	BB
REVISION SCHEDULE	
NO.	DATE   DESCRIPTION

**MAIN FLOOR FRAMING PLAN**

**S-2**



1 MAIN FLOOR  
1/4" = 1'-0"



**2906 74TH AVE SE REMODEL**


2906 74TH AVE SE,  
MERCER ISLAND, WA  
98040

DRAWING INFO

ISSUE DATE	07-25-22
ISSUED FOR	PERMIT
PROJECT NO.	20242
ENGINEER	BB
REVISION SCHEDULE	
NO.	DATE DESCRIPTION

**ROOF FRAMING PLAN**

**S-3**





**2906 74TH AVE SE REMODEL**

2906 74TH AVE SE,  
MERCER ISLAND, WA  
98040


DRAWING INFO

ISSUE DATE 07-25-22  
ISSUED FOR PERMIT  
PROJECT NO. 20242  
ENGINEER BB


REVISION SCHEDULE		
NO.	DATE	DESCRIPTION

**FRAMING DETAILS**


**S-4**



1  
3/4" = 1'-0"



2  
3/4" = 1'-0"





3  
3/4" = 1'-0"

TYPE	PLYWOOD OR OSB SHEATHING (NOTE 7)	PANEL EDGE NAILING (NOTE 4)	PANEL EDGE STUDS AND BLKG	ANCHOR BOLTS AT SILL PLATE (NOTE 8)	TOP/SILL PLATE TO BLOCKING/ RIM (NOTE 9)	BOTTOM PLATE TO BLOCKING/ RIM (NOTE 4)	CAPACITY (LRFD) (SEISMIC/WIND)
SW6	15/32" PLY/OSB ONE SIDE	10d COM AT 6"	2x	5/8" AT 36" O.C.-2x	SIMPSON LTP4 AT 24" O.C.	16d COM AT 6" O.C.-NARROW	496 PLF/ 696 PLF
SW4	15/32" PLY/OSB ONE SIDE	10d COM AT 4"	2x (SEE NOTE 5)	5/8" AT 24" O.C.-2x	SIMPSON LTP4 AT 16" O.C.	16d COM AT 4" O.C.-NARROW	736 PLF/ 1032 PLF
SW3	15/32" PLY/OSB ONE SIDE	10d COM AT 3"	3x	5/8" AT 18" O.C.-2x	SIMPSON LTP4 AT 12" O.C.	16d COM AT 3" O.C.-WIDE	960 PLF/ 1344 PLF
SW2	15/32" PLY/OSB ONE SIDE	10d COM AT 2"	3x	5/8" AT 12" O.C.-2x	SIMPSON LTP4 AT 8" O.C.	16d COM AT 2" O.C.-WIDE	1232 PLF/ 1724 PLF
SW44	15/32" PLY/OSB TWO SIDES	10d COM AT 4"	2x	5/8" AT 18" O.C.-3x	SIMPSON LTP4 AT 16" O.C. B.S.	(2) 16d COM AT 4" O.C.-WIDE	1472 PLF/ 2064 PLF
SW33	15/32" PLY/OSB TWO SIDES	10d COM AT 3"	3x	5/8" AT 16" O.C.-3x	SIMPSON LTP4 AT 12" O.C. B.S.	(2) 16d COM AT 3" O.C.-WIDE	1920 PLF/ 2688 PLF
SW22	15/32" PLY/OSB TWO SIDES	10d COM AT 2"	3x	5/8" AT 12" O.C.-3x	SIMPSON LTP4 AT 8" O.C. B.S.	(2) 16d COM AT 2" O.C.-WIDE	2464 PLF/ 3448 PLF

- SHEARWALL SCHEDULE NOTES:**
- ALL PANEL EDGES TO OCCUR OVER STUDS, PLATES, RIMS OR HORIZONTAL BLOCKING AT WALLS
  - NAIL SHEATHING TO INTERMEDIATE SUPPORTS/ FIELD NAILING 10d AT 12" O.C.
  - ALL NAILS INTO 3x MEMBERS SHALL BE STAGGERED.  
(2)2x STUDS MAY BE USED IN LIEU OF 3x STUDS AT PANEL JOINTS.  
NAIL STUDS TOGETHER W/2 ROWS 16d COMMON AT 6" O.C. AT SINGLE SIDE SHEATHING AND NAIL WITH 2 ROWS OF 16d COMMON AT 3" O.C. AT DOUBLE SHEATHED WALLS.
  - COM DENOTES COMMON NAILS. MIN. NAIL PENETRATION INTO PLATE, RIM OR BLOCKING SHALL BE 1 5/8". STAGGER BOTTOM PLATE NAILING
  - FOR SHEARWALL SW4, ALL FRAMING MEMBERS RECEIVING EDGE NAILINGS FROM ABUTTING PANELS SHALL BE 3x OR (2) 2x NAILED TOGETHER WITH 16d AT 6"
  - WHERE SHEATHING IS APPLIED TO BOTH SIDES OF WALL, OFFSET PANEL EDGES TO FALL ON DIFFERENT STUDS.
  - PROVIDE SHEAR WALL SHEATHING AND NAILING FOR ENTIRE LENGTH OF WALLS NOTED ON PLAN. PROVIDE HOLD-DOWNS PER PLAN AT EACH END OF WALL. UNO.  
PROVIDE (2) 2x STUDS AT ENDS OF ALL SHEARWALL. FACE NAIL MULTIPLE STUDS WITH 16d AT 12"  
PROVIDE PANEL EDGE NAILING IN EACH HOLD-DOWN STUD AT END OF WALL.
  - ALL FOUNDATION SILL PLATES SHALL BE PT MEMBERS AND THE ANCHOR BOLTS SHALL HAVE MIN. OF 7" EMBEDMENT WITH 1/4" x 3" x 3" PLATE WASHER OR SIMPSON'S BP/ BPS PLATE.  
END OF WALL ANCHOR BOLTS SHALL BE LOCATED MAX 12" AND MIN 5" FROM END OF THE PLATE.
  - WHERE NOTED IN DETAILS, USE SIMPSON A35 IN LIEU OF LTP4 PLATES SPACE AT 2/3 OF LTP4 SPACING.
- | SIMPSON HOLD-DOWN | SIMPSON ANCHOR BOLTS*                         | SIMPSON EPOXY ALL THREAD ANCHORS* |
|-------------------|---|-----------------------------------|
| HDU2              | SSTB16 (5/8" ANCHOR WITH 12 5/8" MIN. EMBED.) | 5/8" (12" EMBED WITH SET-XP)      |
| HDU4              | SB 5/8X 24 (5/8" ANCHOR WITH 18" MIN. EMBED.) | 5/8" (14" EMBED WITH SET-XP)      |
| HDU5              | SB 5/8X 24 (5/8" ANCHOR WITH 18" MIN. EMBED.) | 5/8" (16" EMBED WITH SET-XP)      |
| HDU8              | SB 7/8X 24 (7/8" ANCHOR WITH 18" MIN. EMBED.) |                                   |
| HDU11             | SB 1X 30 (1" ANCHOR WITH 24" MIN. EMBED.)     |                                   |
| HDU14             | SB 1X 30 (1" ANCHOR WITH 24" MIN. EMBED.)     |                                   |
- \* ALL ANCHORS SHALL BE 2.5" MIN. FROM EDGE OF CONCRETE WALL

A  
3/4" = 1'-0"



B  
3/4" = 1'-0"