



May 19, 2023

STRUCTURAL CALCULATIONS
(Permit Supplement)

HEADRICK RESIDENCE
8822 SE 62nd Street
Mercer Island, WA 98040



Quantum Job Number: 21271.01

Prepared for:
NED NELSON, ARCHITECT
1021 92nd Avenue NE
Bellevue, Washington 98004

Prepared by:
QUANTUM CONSULTING ENGINEERS
1511 Third Avenue, Suite 323
Seattle, WA 98101
TEL 206.957.3900
FAX 206.957.3901

Project Title:
 Engineer:
 Project ID:
 Project Descr:

Wood Beam

Project File: Headrick Rev 2.ec6

LIC# : KW-06016450, Build:20.23.04.05

QUANTUM CONSULTING ENGINEERS

(c) ENERCALC INC 1983-2023


DESCRIPTION: L2J3 Rev 2 - Deck Joist

CODE REFERENCES

Calculations per NDS 2015, IBC 2015, CBC 2016, ASCE 7-10
 Load Combination Set : IBC 2015

Material Properties

Analysis Method : Allowable Stress Design	Fb +	1,600.0 psi	E : Modulus of Elasticity
Load Combination IBC 2015	Fb -	1,600.0 psi	Ebend- xx
	Fc - Prll	1,100.0 psi	Eminbend - xx
Wood Species : Douglas Fir - Larch	Fc - Perp	625.0 psi	
Wood Grade : Select structural	Fv	170.0 psi	
	Ft	950.0 psi	Density
Beam Bracing : Beam is Fully Braced against lateral-torsional buckling			31.20pcf



Applied Loads

Service loads entered. Load Factors will be applied for calculations.

Beam self weight calculated and added to loading
 Uniform Load : D = 0.0120, L = 0.060 ksf, Tributary Width = 3.50 ft, (Deck)

DESIGN SUMMARY

Design OK

Maximum Bending Stress Ratio	=	0.865 : 1	Maximum Shear Stress Ratio	=	0.344 : 1
Section used for this span		6x8	Section used for this span		6x8
fb: Actual	=	1,383.44 psi	fv: Actual	=	58.44 psi
F'b	=	1,600.00 psi	F'v	=	170.00 psi
Load Combination		+D+L	Load Combination		+D+L
Location of maximum on span	=	6.750ft	Location of maximum on span	=	0.000ft
Span # where maximum occurs	=	Span # 1	Span # where maximum occurs	=	Span # 1
Maximum Deflection					
Max Downward Transient Deflection	0.510 in	Ratio = 317 >=240	Span: 1 : L Only		
Max Upward Transient Deflection	0 in	Ratio = 0 <240	n/a		
Max Downward Total Deflection	0.634 in	Ratio = 255 >=180	Span: 1 : +D+L		
Max Upward Total Deflection	0 in	Ratio = 0 <180	n/a		

Maximum Forces & Stresses for Load Combinations

Load Combination	Segment Length	Span #	Max Stress Ratios										Moment Values			Shear Values					
			M	V	CD	CM	C _t	CLx	C _F	C _{fu}	C _i	C _r	M	fb	F'b	V	fv	F'v			
D Only																					
	Length = 13.451 ft	1	0.188	0.075	0.90	1.00	1.00	1.00	1.000	1.00	1.00	1.00	1.16	270.1	1,440.0	0.00	0.00	0.0	0.0	0.0	
	Length = 0.04927 ft	1	0.003	0.075	0.90	1.00	1.00	1.00	1.000	1.00	1.00	1.00	0.02	3.9	1,440.0	0.31	11.4	153.0	0.31	11.4	153.0
+D+L																					
	Length = 13.451 ft	1	0.865	0.344	1.00	1.00	1.00	1.00	1.000	1.00	1.00	1.00	5.94	1,383.4	1,600.0	1.61	58.4	170.0	1.61	58.4	170.0
	Length = 0.04927 ft	1	0.013	0.344	1.00	1.00	1.00	1.00	1.000	1.00	1.00	1.00	0.09	20.1	1,600.0	1.61	58.4	170.0	1.61	58.4	170.0
+D+0.750L																					
	Length = 13.451 ft	1	0.553	0.220	1.25	1.00	1.00	1.00	1.000	1.00	1.00	1.00	4.75	1,105.1	2,000.0	1.28	46.7	212.5	1.28	46.7	212.5
	Length = 0.04927 ft	1	0.008	0.220	1.25	1.00	1.00	1.00	1.000	1.00	1.00	1.00	0.07	16.1	2,000.0	1.28	46.7	212.5	1.28	46.7	212.5
+0.60D																					
																0.0	0.00	0.0	0.0	0.0	0.0

Project Title:
 Engineer:
 Project ID:
 Project Descr:

Wood Beam

Project File: Headrick Rev 2.ec6

LIC# : KW-06016450, Build:20.23.04.05

QUANTUM CONSULTING ENGINEERS

(c) ENERCALC INC 1983-2023

DESCRIPTION: L2J3 Rev 2 - Deck Joist

Maximum Forces & Stresses for Load Combinations

Load Combination	Max Stress Ratios											Moment Values			Shear Values		
Segment Length	Span #	M	V	CD	CM	C _t	CLx	C _F	C _{fu}	C _i	C _r	M	fb	F'b	V	fv	F'v
Length = 13.451 ft	1	0.063	0.025	1.60	1.00	1.00	1.00	1.000	1.00	1.00	1.00	0.70	162.0	2,560.0	0.19	6.8	272.0
Length = 0.04927 ft	1	0.001	0.025	1.60	1.00	1.00	1.00	1.000	1.00	1.00	1.00	0.01	2.4	2,560.0	0.19	6.8	272.0

Overall Maximum Deflections

Load Combination	Span	Max. "-" Defl	Location in Span	Load Combination	Max. "+" Defl	Location in Span
+D+L	1	0.6340	6.799		0.0000	0.000

Vertical Reactions

Load Combination	Support notation : Far left is #1		Values in KIPS	
	Support 1	Support 2		
Max Upward from all Load Conditions	1.761	1.761		
Max Upward from Load Combinations	1.761	1.761		
Max Upward from Load Cases	1.418	1.418		
D Only	0.344	0.344		
+D+L	1.761	1.761		
+D+0.750L	1.407	1.407		
+0.60D	0.206	0.206		
L Only	1.418	1.418		

Second Level			
Member Name	Results	Current Solution	Comments
L2B3. - Deck Rev 2	Passed	1 piece(s) 6 3/4" x 15" 24F-V4 DF Glulam	

ForteWEB Software Operator	Job Notes
Maxwell Skotheim Quantum Consulting Engineers (206) 957-3906 MSkotheim@quantumce.com	




5/19/2023 6:36:35 PM UTC

ForteWEB v3.5

File Name: 21271.01 - Headrick Residence

Second Level, L2B3. - Deck Rev 2
 1 piece(s) 6 3/4" x 15" 24F-V4 DF Glulam



All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal.

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	5585 @ 22' 2"	6581 (1.50")	Passed (85%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	4947 @ 20' 11"	17888	Passed (28%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	30542 @ 11' 2 3/4"	47967	Passed (64%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.611 @ 11' 2 3/4"	0.729	Passed (L/430)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.770 @ 11' 2 3/4"	1.094	Passed (L/341)	--	1.0 D + 1.0 L (All Spans)

System : Floor
 Member Type : Flush Beam
 Building Use : Residential
 Building Code : IBC 2018
 Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume factor of 0.95 that was calculated using length L = 21' 10 1/2".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.00"	3.25"	2.07"	1182	4548	5730	1 3/4" Rim Board
2 - Hanger on 15" HF beam	2.00"	Hanger ¹	1.50"	1169	4497	5666	See note ¹

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	22' o/c	
Bottom Edge (Lu)	22' o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie						
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
2 - Face Mount Hanger	HGUS6.88/12	4.00"	N/A	56-10d	20-10d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	1 3/4" to 22' 2"	N/A	24.6	--	
1 - Uniform (PSF)	0 to 22' 4" (Front)	6' 9"	12.0	60.0	Deck

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.eyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Maxwell Skotheim Quantum Consulting Engineers (206) 957-3906 MSkotheim@quantumce.com	

