



## Structural Calculations


(Response to Review Corrections)


Project: **Mounger Residence**  
4006 E. Mercer Way  
Mercer Island, WA 98040


For: **Sturman Architects**  
9 - 103<sup>rd</sup> Ave SE, Suite 203  
Bellevue, WA 98004

By: **Année Structural Engineering, LLC**  
1801 18<sup>th</sup> Ave S  
Seattle, WA 98144

Date: **August 29, 2022**







Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 12:58PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: South basement entry wasl

Calculations per ACI 318-11, ACI 530-11, IBC 2012,  
 CBC 2013, ASCE 7-10

### Criteria

Retained Height	=	5.33 ft
Wall height above soil	=	0.50 ft
Slope Behind Wall	=	0.00 : 1
Height of Soil over Toe	=	4.00 in
Water height over heel	=	0.0 ft
Vertical component of active Lateral soil pressure options:		
NOT USED for Soil Pressure.		
NOT USED for Sliding Resistance.		
NOT USED for Overturning Resistance.		

### Soil Data

Allow Soil Bearing	=	2,000.0 psf
Equivalent Fluid Pressure Method		
Heel Active Pressure	=	35.0 psf/ft
Toe Active Pressure	=	35.0 psf/ft
Passive Pressure	=	250.0 psf/ft
Soil Density, Heel	=	120.00 pcf
Soil Density, Toe	=	120.00 pcf
Friction Coeff btwn Ftg & Soil	=	0.350
Soil height to ignore for passive pressure	=	0.00 in

### Surcharge Loads

Surcharge Over Heel	=	0.0 psf
Used To Resist Sliding & Overturning		
Surcharge Over Toe	=	50.0 psf
Used for Sliding & Overturning		

### Axial Load Applied to Stem

Axial Dead Load	=	0.0 lbs
Axial Live Load	=	0.0 lbs
Axial Load Eccentricity	=	0.0 in

### Design Summary

#### Wall Stability Ratios

Overturning	=	1.97 OK
Sliding	=	1.58 OK
<i>Slab Resists All Sliding !</i>		
Total Bearing Load	=	1,625 lbs
...resultant ecc.	=	6.95 in
Soil Pressure @ Toe	=	1,079 psf OK
Soil Pressure @ Heel	=	0 psf OK
Allowable	=	2,000 psf
<i>Soil Pressure Less Than Allowable</i>		
ACI Factored @ Toe	=	1,295 psf
ACI Factored @ Heel	=	0 psf
Footing Shear @ Toe	=	5.0 psi OK
Footing Shear @ Heel	=	2.1 psi OK
Allowable	=	75.0 psi
<b>Sliding Calcs</b> Slab Resists All Sliding !		
Lateral Sliding Force	=	704.8 lbs
less 100% Passive Force	=	- 542.5 lbs
less 100% Friction Force	=	- 568.8 lbs
Added Force Req'd	=	0.0 lbs OK
...for 1.5 : 1 Stability	=	0.0 lbs OK

#### Load Factors

Dead Load	1.200
Live Load	1.600
Earth, H	1.600
Wind, W	1.600
Seismic, E	1.000

### Lateral Load Applied to Stem

Lateral Load	=	0.0 plf
...Height to Top	=	5.33 ft
...Height to Bottom	=	0.00 ft

Wind on Exposed Stem = 0.0 psf

### Stem Construction

#### Design Height Above Ftg

Design Height Above Ftg	ft =	0.00
Wall Material Above "Ht"	=	Concrete
Thickness	in =	8.00
Rebar Size	=	# 4
Rebar Spacing	in =	12.00
Rebar Placed at	=	Center

#### Design Data

fb/FB + fa/Fa	=	0.417
Total Force @ Section	lbs =	785.5
Moment....Actual	ft-l =	1,414.0
Moment....Allowable	ft-l =	3,387.6
Shear.....Actual	psi =	16.4
Shear.....Allowable	psi =	75.0
Wall Weight	psf =	100.0
Rebar Depth 'd'	in =	4.00
Lap splice if above	in =	18.72
Lap splice if below	in =	8.40
Hook embed into footing	in =	8.40

#### Concrete Data

f'c	psi =	2,500.0
Fy	psi =	

### Adjacent Footing Load

Adjacent Footing Load	=	0.0 lbs
Footing Width	=	0.00 ft
Eccentricity	=	0.00 in
Wall to Ftg CL Dist	=	0.00 ft
Footing Type		Line Load
Base Above/Below Soil at Back of Wall	=	0.0 ft
Poisson's Ratio	=	0.300

#### Top Stem

Stem OK

Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 12:58PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. # : KW-06009341

Licensee : Annee Structural Engineering LLC

Description : South basement entry wasl

### Footing Dimensions & Strengths

Toe Width	=	2.17	ft
Heel Width	=	1.00	
Total Footing Width	=	3.17	
Footing Thickness	=	16.00	in
Key Width	=	0.00	in
Key Depth	=	0.00	in
Key Distance from Toe	=	0.00	ft
$f_c$	=	2,500	psi
$F_y$	=	60,000	psi
Footing Concrete Density	=	150.00	pcf
Min. As %	=	0.0018	
Cover @ Top	=	2.00	
@ Btm.	=	3.00	in

### Footing Design Results

	Toe	Heel
Factored Pressure	= 1,295	0 psf
Mu' : Upward	= 0	0 ft-lb
Mu' : Downward	= 0	56 ft-lb
Mu: Design	= 1,414	56 ft-lb
Actual 1-Way Shear	= 5.02	2.07 psi
Allow 1-Way Shear	= 75.00	75.00 psi
Toe Reinforcing	= None Spec'd	
Heel Reinforcing	= None Spec'd	
Key Reinforcing	= None Spec'd	



#### Other Acceptable Sizes & Spacings

Toe: Not req'd,  $M_u < S * F_r$   
 Heel: Not req'd,  $M_u < S * F_r$   
 Key: No key defined

### Summary of Overturning & Resisting Forces & Moments

Item	.....OVERTURNING.....			.....RESISTING.....			
	Force lbs	Distance ft	Moment ft-lb	Force lbs	Distance ft	Moment ft-lb	
Heel Active Pressure	= 777.7	2.22	1,728.1	Soil Over Heel	= 213.3	3.00	640.0
Surcharge over Heel	=			Sloped Soil Over Heel	=		
Toe Active Pressure	= -48.6	0.56	-27.0	Surcharge Over Heel	=		
Surcharge Over Toe	= -24.3	0.83	-20.3	Adjacent Footing Load	=		
Adjacent Footing Load	=			Axial Dead Load on Stem	=		
Added Lateral Load	=			* Axial Live Load on Stem	=		
Load @ Stem Above Soil	=			Soil Over Toe	= 86.7	1.08	93.9
				Surcharge Over Toe	= 108.4	1.08	117.4
				Stem Weight(s)	= 583.3	2.50	1,458.4
				Earth @ Stem Transitions	=		
				Footing Weight	= 633.4	1.58	1,003.0
				Key Weight	=		
				Vert. Component	=		
<b>Total</b>	= 704.8	<b>O.T.M.</b>	= 1,680.9	<b>Total</b>	= 1,625.1	<b>lbs R.M.</b>	= 3,312.8
<b>Resisting/Overturning Ratio</b>		=	<b>1.97</b>				
Vertical Loads used for Soil Pressure	=	1,625.1	lbs				

\* Axial live load NOT included in total displayed, or used for overturning resistance, but is included for soil pressure calculation.




$$R_1 = \frac{24.67'}{22"} (1.625') = 1.82 \text{ k/ft}$$

$$S_1 = 20.0 \text{ k} / 1.82 \text{ k/ft} = 11'-0" \text{ oc (4" } \phi \text{ piles)}$$

$$R_2 = \frac{16.46'}{22"} (1.625') = 1.22 \text{ k/ft}$$

$$S_2 = 20.0 / 1.22 = 16'-5" \text{ oc (4" } \phi \text{ piles)}$$



Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 12:56PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: South basement entry wasl

Calculations per ACI 318-11, ACI 530-11, IBC 2012,  
 CBC 2013, ASCE 7-10

### Criteria

Retained Height = 5.33 ft  
 Wall height above soil = 0.50 ft  
 Slope Behind Wall = 0.00 : 1  
 Height of Soil over Toe = 4.00 in  
 Water height over heel = 0.0 ft  
 Vertical component of active  
 Lateral soil pressure options:  
 NOT USED for Soil Pressure.  
 NOT USED for Sliding Resistance.  
 NOT USED for Overturning Resistance.

### Soil Data

Allow Soil Bearing = 2,000.0 psf  
 Equivalent Fluid Pressure Method  
 Heel Active Pressure = 35.0 psf/ft  
 Toe Active Pressure = 35.0 psf/ft  
 Passive Pressure = 250.0 psf/ft  
 Soil Density, Heel = 120.00 pcf  
 Soil Density, Toe = 120.00 pcf  
 Friction Coeff btwn Ftg & Soil = 0.350  
 Soil height to ignore  
 for passive pressure = 0.00 in

### Surcharge Loads

Surcharge Over Heel = 0.0 psf  
 Used To Resist Sliding & Overturning  
 Surcharge Over Toe = 50.0 psf  
 Used for Sliding & Overturning

### Axial Load Applied to Stem

Axial Dead Load = 0.0 lbs  
 Axial Live Load = 0.0 lbs  
 Axial Load Eccentricity = 0.0 in

### Lateral Load Applied to Stem

Lateral Load = 42.7 plf  
 ...Height to Top = 5.33 ft  
 ...Height to Bottom = 0.00 ft

### Adjacent Footing Load

Adjacent Footing Load = 0.0 lbs  
 Footing Width = 0.00 ft  
 Eccentricity = 0.00 in  
 Wall to Ftg CL Dist = 0.00 ft  
 Footing Type = Line Load  
 Base Above/Below Soil = 0.0 ft  
 at Back of Wall  
 Poisson's Ratio = 0.300

### Design Summary

#### Wall Stability Ratios

Overturning = 1.28 Ratio < 1.5!  
 Sliding = 1.19 Ratio < 1.5!  
*Slab Resists All Sliding!*  
 Total Bearing Load = 1,625 lbs  
 ...resultant ecc. = 13.67 in

Soil Pressure @ Toe = 2,437 psf NG  
 Soil Pressure @ Heel = 0 psf OK  
 Allowable = 2,000 psf  
*Soil Pressure Exceeds Allowable!*

ACI Factored @ Toe = 2,924 psf  
 ACI Factored @ Heel = 0 psf  
 Footing Shear @ Toe = 9.8 psi OK  
 Footing Shear @ Heel = 2.1 psi OK  
 Allowable = 75.0 psi

#### Sliding Calcs Slab Resists All Sliding!

Lateral Sliding Force = 932.2 lbs  
 less 100% Passive Force = - 542.5 lbs  
 less 100% Friction Force = - 568.8 lbs  
 Added Force Req'd = 0.0 lbs OK  
 ...for 1.5 : 1 Stability = 287.0 lbs NG

#### Load Factors

Dead Load 1.200  
 Live Load 1.600  
 Earth, H 1.600  
 Wind, W 1.600  
 Seismic, E 1.000

### Stem Construction

#### Design Height Above Ftg

Wall Material Above "Ht" = Concrete  
 Thickness = 8.00 in  
 Rebar Size = # 4  
 Rebar Spacing = 12.00 in  
 Rebar Placed at = Center

#### Design Data

fb/FB + fa/Fa = 0.596  
 Total Force @ Section = 1,012.9 lbs  
 Moment....Actual = 2,020.1 ft-l  
 Moment....Allowable = 3,387.6 ft-l  
 Shear.....Actual = 21.1 psi  
 Shear.....Allowable = 75.0 psi  
 Wall Weight = 100.0 psf  
 Rebar Depth 'd' = 4.00 in  
 Lap splice if above = 18.72 in  
 Lap splice if below = 8.40 in  
 Hook embed into footing = 8.40 in

#### Concrete Data

f'c = 2,500.0 psi  
 Fy = psi

#### Top Stem

Stem OK

Factor of Safety for Seismic loading is 1.2 per geotech and soil  
 bearing pressure has a 1/3 increase for seismic loads per geotech.  
 This is typical at wall calculations.



Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 12:56PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: South basement entry wasl

### Footing Dimensions & Strengths

Toe Width = 2.17 ft  
 Heel Width = 1.00  
 Total Footing Width = 3.17  
 Footing Thickness = 16.00 in  
 Key Width = 0.00 in  
 Key Depth = 0.00 in  
 Key Distance from Toe = 0.00 ft  
 f<sub>c</sub> = 2,500 psi F<sub>y</sub> = 60,000 psi  
 Footing Concrete Density = 150.00 pcf  
 Min. As % = 0.0018  
 Cover @ Top 2.00 @ Btm. = 3.00 in

### Footing Design Results


	<u>Toe</u>	<u>Heel</u>
Factored Pressure	= 2,924	0 psf
Mu' : Upward	= 0	0 ft-lb
Mu' : Downward	= 0	56 ft-lb
Mu: Design	= 2,020	56 ft-lb
Actual 1-Way Shear	= 9.80	2.07 psi
Allow 1-Way Shear	= 75.00	75.00 psi
Toe Reinforcing	= None Spec'd	
Heel Reinforcing	= None Spec'd	
Key Reinforcing	= None Spec'd	


Other Acceptable Sizes & Spacings  
 Toe: Not req'd, Mu < S \* Fr  
 Heel: Not req'd, Mu < S \* Fr  
 Key: No key defined

### Summary of Overturning & Resisting Forces & Moments

Item	.....OVERTURNING.....				.....RESISTING.....		
	Force lbs	Distance ft	Moment ft-lb		Force lbs	Distance ft	Moment ft-lb
Heel Active Pressure	= 777.7	2.22	1,728.1	Soil Over Heel	= 213.3	3.00	640.0
Surcharge over Heel	=			Sloped Soil Over Heel	=		
Toe Active Pressure	= -48.6	0.56	-27.0	Surcharge Over Heel	=		
Surcharge Over Toe	= -24.3	0.83	-20.3	Adjacent Footing Load	=		
Adjacent Footing Load	=			Axial Dead Load on Stem	=		
Added Lateral Load	= 227.4	4.00	909.3	* Axial Live Load on Stem	=		
Load @ Stem Above Soil	=			Soil Over Toe	= 86.7	1.08	93.9
				Surcharge Over Toe	= 108.4	1.08	117.4
				Stem Weight(s)	= 583.3	2.50	1,458.4
				Earth @ Stem Transitions	=		
				Footing Weight	= 633.4	1.58	1,003.0
				Key Weight	=		
				Vert. Component	=		
<b>Total</b>	= 932.2	<b>O.T.M.</b>	= 2,590.2	<b>Total</b>	= 1,625.1 lbs	<b>R.M.</b>	= 3,312.8
<b>Resisting/Overturning Ratio</b>			= <b>1.28</b>				
Vertical Loads used for Soil Pressure			= 1,625.1 lbs				

\* Axial live load NOT included in total displayed, or used for overturning resistance, but is included for soil pressure calculation.





Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:04PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: 5' landscape wall - west of garage - 10/S3.3

Calculations per ACI 318-11, ACI 530-11, IBC 2012,  
 CBC 2013, ASCE 7-10

### Criteria

Retained Height	=	6.77 ft
Wall height above soil	=	0.50 ft
Slope Behind Wall	=	0.00 : 1
Height of Soil over Toe	=	4.00 in
Water height over heel	=	0.0 ft
Vertical component of active Lateral soil pressure options:		
NOT USED for Soil Pressure.		
NOT USED for Sliding Resistance.		
NOT USED for Overturning Resistance.		

### Soil Data

Allow Soil Bearing	=	2,000.0 psf
Equivalent Fluid Pressure Method		
Heel Active Pressure	=	55.0 psf/ft
Toe Active Pressure	=	55.0 psf/ft
Passive Pressure	=	250.0 psf/ft
Soil Density, Heel	=	120.00 pcf
Soil Density, Toe	=	120.00 pcf
Friction Coeff btwn Ftg & Soil	=	0.350
Soil height to ignore for passive pressure	=	0.00 in

55 pcf for this particular slope  
 per geotech.

### Surcharge Loads

Surcharge Over Heel	=	0.0 psf
Used To Resist Sliding & Overturning		
Surcharge Over Toe	=	50.0 psf
Used for Sliding & Overturning		

### Lateral Load Applied to Stem

Lateral Load	=	0.0 plf
...Height to Top	=	6.77 ft
...Height to Bottom	=	0.00 ft

### Adjacent Footing Load

Adjacent Footing Load	=	0.0 lbs
Footing Width	=	0.00 ft
Eccentricity	=	0.00 in
Wall to Ftg CL Dist	=	0.00 ft
Footing Type		Line Load
Base Above/Below Soil at Back of Wall	=	0.0 ft
Poisson's Ratio	=	0.300

### Axial Load Applied to Stem

Axial Dead Load	=	0.0 lbs
Axial Live Load	=	0.0 lbs
Axial Load Eccentricity	=	0.0 in

Wind on Exposed Stem = 0.0 psf

### Design Summary

#### Wall Stability Ratios

Overturning	=	1.77 OK
Sliding	=	0.77 UNSTABLE!
<i>Slab Resists All Sliding!</i>		
Total Bearing Load	=	2,441 lbs
...resultant ecc.	=	10.91 in
Soil Pressure @ Toe	=	1,295 psf OK
Soil Pressure @ Heel	=	0 psf OK
Allowable	=	2,000 psf
<i>Soil Pressure Less Than Allowable</i>		
ACI Factored @ Toe	=	1,554 psf
ACI Factored @ Heel	=	0 psf
Footing Shear @ Toe	=	21.5 psi OK
Footing Shear @ Heel	=	14.6 psi OK
Allowable	=	75.0 psi

#### Sliding Calcs Slab Resists All Sliding!

Lateral Sliding Force	=	1,525.6 lbs
less 100% Passive Force	= -	313.4 lbs
less 100% Friction Force	= -	850.0 lbs
Added Force Req'd	=	357.9 lbs NG
...for 1.5 : 1 Stability	=	1,120.7 lbs NG

#### Load Factors

Dead Load	1.200
Live Load	1.600
Earth, H	1.600
Wind, W	1.600
Seismic, E	1.000

### Stem Construction

#### Design Height Above Ftg

Design Height Above Ftg	ft =	0.00
Wall Material Above "H"	=	Concrete
Thickness	in =	8.00
Rebar Size	=	# 4
Rebar Spacing	in =	9.00
Rebar Placed at	=	Edge

#### Design Data

fb/FB + fa/Fa	=	0.639
Total Force @ Section	lbs =	1,999.5
Moment....Actual	ft-l =	4,548.3
Moment....Allowable	ft-l =	7,122.4
Shear.....Actual	psi =	26.7
Shear.....Allowable	psi =	75.0
Wall Weight	psf =	100.0
Rebar Depth 'd'	in =	6.25
Lap splice if above	in =	18.72
Lap splice if below	in =	6.00
Hook embed into footing	in =	6.00

#### Concrete Data

f'c	psi =	2,500.0
Fy	psi =	

#### Top Stem

Stem OK

Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:04PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: 5' landscape wall - west of garage - 10/S3.3

### Footing Dimensions & Strengths

Toe Width	=	2.50	ft
Heel Width	=	1.83	
Total Footing Width	=	4.33	
Footing Thickness	=	10.00	in
Key Width	=	0.00	in
Key Depth	=	0.00	in
Key Distance from Toe	=	0.00	ft
$f_c$	=	2,500	psi
$F_y$	=	60,000	psi
Footing Concrete Density	=	150.00	pcf
Min. As %	=	0.0018	
Cover @ Top	=	2.00	
@ Btm.	=	3.00	in

### Footing Design Results

	Toe	Heel
Factored Pressure	= 1,554	0 psf
$\mu_u$ : Upward	= 3,782	0 ft-lb
$\mu_u$ : Downward	= 869	765 ft-lb
$\mu_u$ : Design	= 2,913	765 ft-lb
Actual 1-Way Shear	= 21.50	14.58 psi
Allow 1-Way Shear	= 75.00	75.00 psi
Toe Reinforcing	= # 4 @ 9.00 in	
Heel Reinforcing	= None Spec'd	
Key Reinforcing	= None Spec'd	


#### Other Acceptable Sizes & Spacings


Toe: #4@ 17.25 in, #5@ 26.50 in, #6@ 37.75 in, #7@ 48.25 in, #8@ 48.25 in, #9@ 4  
 Heel: Not req'd,  $\mu_u < S * Fr$   
 Key: No key defined

### Summary of Overturning & Resisting Forces & Moments

Item	.....OVERTURNING.....			.....RESISTING.....			
	Force lbs	Distance ft	Moment ft-lb	Force lbs	Distance ft	Moment ft-lb	
Heel Active Pressure	= 1,589.8	2.53	4,029.2	Soil Over Heel	= 947.5	3.75	3,553.1
Surcharge over Heel	=			Sloped Soil Over Heel	=		
Toe Active Pressure	= -37.4	0.39	-14.6	Surcharge Over Heel	=		
Surcharge Over Toe	= -26.7	0.58	-15.6	Adjacent Footing Load	=		
Adjacent Footing Load	=			Axial Dead Load on Stem	=		
Added Lateral Load	=			* Axial Live Load on Stem	=		
Load @ Stem Above Soil	=			Soil Over Toe	= 100.0	1.25	125.0
				Surcharge Over Toe	= 125.0	1.25	156.3
				Stem Weight(s)	= 727.0	2.83	2,059.8
				Earth @ Stem Transitions	=		
				Footing Weight	= 541.6	2.17	1,173.4
				Key Weight	=		
				Vert. Component	=		
<b>Total</b>	= 1,525.6	<b>O.T.M.</b>	= 3,999.1	<b>Total</b>	= 2,441.2 lbs	<b>R.M.</b>	= 7,067.6
<b>Resisting/Overturning Ratio</b>		=	<b>1.77</b>				
Vertical Loads used for Soil Pressure	=	2,441.2	lbs				

\* Axial live load NOT included in total displayed, or used for overturning resistance, but is included for soil pressure calculation.





Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:02PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. # : KW-06009341

Licensee : Annee Structural Engineering LLC

Description : 5' landscape wall - west of garage - 10/S3.3

Calculations per ACI 318-11, ACI 530-11, IBC 2012,  
 CBC 2013, ASCE 7-10

### Criteria

Retained Height	=	6.77 ft
Wall height above soil	=	0.50 ft
Slope Behind Wall	=	0.00 : 1
Height of Soil over Toe	=	4.00 in
Water height over heel	=	0.0 ft
Vertical component of active Lateral soil pressure options:		
NOT USED for Soil Pressure.		
NOT USED for Sliding Resistance.		
NOT USED for Overturning Resistance.		

### Soil Data

Allow Soil Bearing	=	2,000.0 psf
Equivalent Fluid Pressure Method		
Heel Active Pressure	=	55.0 psf/ft
Toe Active Pressure	=	55.0 psf/ft
Passive Pressure	=	250.0 psf/ft
Soil Density, Heel	=	120.00 pcf
Soil Density, Toe	=	120.00 pcf
Friction Coeff btwn Ftg & Soil	=	0.350
Soil height to ignore for passive pressure	=	0.00 in

### Surcharge Loads

Surcharge Over Heel	=	0.0 psf
Used To Resist Sliding & Overturning		
Surcharge Over Toe	=	50.0 psf
Used for Sliding & Overturning		

### Axial Load Applied to Stem

Axial Dead Load	=	0.0 lbs
Axial Live Load	=	0.0 lbs
Axial Load Eccentricity	=	0.0 in

### Design Summary

#### Wall Stability Ratios

Overturning	=	1.27 Ratio < 1.5!
Sliding	=	0.62 UNSTABLE!
<i>Slab Resists All Sliding !</i>		
Total Bearing Load	=	2,441 lbs
...resultant ecc.	=	18.52 in
Soil Pressure @ Toe	=	2,611 psf NG
Soil Pressure @ Heel	=	0 psf OK
Allowable	=	2,000 psf
<i>Soil Pressure Exceeds Allowable!</i>		
ACI Factored @ Toe	=	3,133 psf
ACI Factored @ Heel	=	0 psf
Footing Shear @ Toe	=	30.2 psi OK
Footing Shear @ Heel	=	14.6 psi OK
Allowable	=	75.0 psi

#### Sliding Calcs Slab Resists All Sliding !

Lateral Sliding Force	=	1,892.3 lbs
less 100% Passive Force	= -	313.4 lbs
less 100% Friction Force	= -	850.0 lbs
Added Force Req'd	=	724.5 lbs NG
...for 1.5 : 1 Stability	=	1,670.7 lbs NG

#### Load Factors

Dead Load	1.200
Live Load	1.600
Earth, H	1.600
Wind, W	1.600
Seismic, E	1.000

### Lateral Load Applied to Stem

Lateral Load	=	54.2 plf
...Height to Top	=	6.77 ft
...Height to Bottom	=	0.00 ft

Wind on Exposed Stem = 0.0 psf

### Stem Construction

#### Design Height Above Ftg

Wall Material Above "Ht"	=	Concrete
Thickness	=	8.00 in
Rebar Size	=	# 4
Rebar Spacing	=	9.00 in
Rebar Placed at	=	Edge

#### Design Data

fb/FB + fa/Fa	=	0.813
Total Force @ Section	lbs =	2,366.2
Moment....Actual	ft-l =	5,789.5
Moment....Allowable	ft-l =	7,122.4
Shear.....Actual	psi =	31.5
Shear.....Allowable	psi =	75.0
Wall Weight	psf =	100.0
Rebar Depth 'd'	in =	6.25
Lap splice if above	in =	18.72
Lap splice if below	in =	6.76
Hook embed into footing	in =	6.76

#### Concrete Data

f'c	psi =	2,500.0
Fy	psi =	

### Adjacent Footing Load

Adjacent Footing Load	=	0.0 lbs
Footing Width	=	0.00 ft
Eccentricity	=	0.00 in
Wall to Ftg CL Dist	=	0.00 ft
Footing Type		Line Load
Base Above/Below Soil at Back of Wall	=	0.0 ft
Poisson's Ratio	=	0.300

#### Top Stem

Stem OK		
ft =	0.00	
ft =	Concrete	
in =	8.00	
=	# 4	
in =	9.00	
=	Edge	



Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:02PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: 5' landscape wall - west of garage - 10/S3.3

### Footing Dimensions & Strengths

Toe Width	=	2.50 ft
Heel Width	=	1.83
Total Footing Width	=	4.33
Footing Thickness	=	10.00 in
Key Width	=	0.00 in
Key Depth	=	0.00 in
Key Distance from Toe	=	0.00 ft
$f_c$	=	2,500 psi
$F_y$	=	60,000 psi
Footing Concrete Density	=	150.00 pcf
Min. As %	=	0.0018
Cover @ Top	2.00	@ Btm. = 3.00 in

### Footing Design Results

	Toe	Heel
Factored Pressure	= 3,133	0 psf
$\mu_u$ : Upward	= 6,527	0 ft-lb
$\mu_u$ : Downward	= 869	765 ft-lb
$\mu_u$ : Design	= 5,658	765 ft-lb
Actual 1-Way Shear	= 30.17	14.58 psi
Allow 1-Way Shear	= 75.00	75.00 psi
Toe Reinforcing	= # 4 @ 9.00 in	
Heel Reinforcing	= None Spec'd	
Key Reinforcing	= None Spec'd	


#### Other Acceptable Sizes & Spacings

Toe: #4@ 9.25 in, #5@ 14.50 in, #6@ 20.50 in, #7@ 27.75 in, #8@ 36.50 in, #9@ 46  
 Heel: Not req'd,  $\mu_u < S * Fr$   
 Key: No key defined


### Summary of Overturning & Resisting Forces & Moments

Item	.....OVERTURNING.....			.....RESISTING.....			
	Force lbs	Distance ft	Moment ft-lb	Force lbs	Distance ft	Moment ft-lb	
Heel Active Pressure	= 1,589.8	2.53	4,029.2	Soil Over Heel	= 947.5	3.75	3,553.1
Surcharge over Heel	=			Sloped Soil Over Heel	=		
Toe Active Pressure	= -37.4	0.39	-14.6	Surcharge Over Heel	=		
Surcharge Over Toe	= -26.7	0.58	-15.6	Adjacent Footing Load	=		
Adjacent Footing Load	=			Axial Dead Load on Stem	=		
Added Lateral Load	= 366.7	4.22	1,546.7	* Axial Live Load on Stem	=		
Load @ Stem Above Soil	=			Soil Over Toe	= 100.0	1.25	125.0
				Surcharge Over Toe	= 125.0	1.25	156.3
				Stem Weight(s)	= 727.0	2.83	2,059.8
				Earth @ Stem Transitions	=		
				Footing Weight	= 541.6	2.17	1,173.4
				Key Weight	=		
				Vert. Component	=		
<b>Total</b>	= 1,892.3	<b>O.T.M.</b>	= 5,545.8	<b>Total</b>	= 2,441.2 lbs	<b>R.M.</b>	= 7,067.6
<b>Resisting/Overturning Ratio</b>		=	<b>1.27</b>				
Vertical Loads used for Soil Pressure	=	2,441.2 lbs					

\* Axial live load NOT included in total displayed, or used for overturning resistance, but is included for soil pressure calculation.



Detail 9/S3.2



Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:13PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. # : KW-06009341

Licensee : Annee Structural Engineering LLC

Description : 10' landscape wall - west of garage - 9/S3.2

Calculations per ACI 318-11, ACI 530-11, IBC 2012,  
 CBC 2013, ASCE 7-10

### Criteria

Retained Height	=	10.10 ft
Wall height above soil	=	0.50 ft
Slope Behind Wall	=	0.00 : 1
Height of Soil over Toe	=	4.00 in
Water height over heel	=	0.0 ft
Vertical component of active Lateral soil pressure options:		
NOT USED for Soil Pressure.		
NOT USED for Sliding Resistance.		
NOT USED for Overturning Resistance.		

### Soil Data

Allow Soil Bearing	=	2,000.0 psf
Equivalent Fluid Pressure Method		
Heel Active Pressure	=	50.0 psf/ft
Toe Active Pressure	=	50.0 psf/ft
Passive Pressure	=	250.0 psf/ft
Soil Density, Heel	=	120.00 pcf
Soil Density, Toe	=	120.00 pcf
Friction Coeff btwn Ftg & Soil	=	0.350
Soil height to ignore for passive pressure	=	0.00 in

maximum 2H:1V slope behind wall.

### Surcharge Loads

Surcharge Over Heel	=	0.0 psf
Used To Resist Sliding & Overturning		
Surcharge Over Toe	=	50.0 psf
Used for Sliding & Overturning		

### Axial Load Applied to Stem

Axial Dead Load	=	0.0 lbs
Axial Live Load	=	0.0 lbs
Axial Load Eccentricity	=	0.0 in

### Lateral Load Applied to Stem

Lateral Load	=	0.0 plf
...Height to Top	=	10.10 ft
...Height to Bottom	=	0.00 ft

### Adjacent Footing Load

Adjacent Footing Load	=	0.0 lbs
Footing Width	=	0.00 ft
Eccentricity	=	0.00 in
Wall to Ftg CL Dist	=	0.00 ft
Footing Type		Line Load
Base Above/Below Soil at Back of Wall	=	0.0 ft
Poisson's Ratio	=	0.300

### Design Summary

#### Wall Stability Ratios

Overturning	=	1.85 OK
Sliding	=	0.62 UNSTABLE!
<i>Slab Resists All Sliding !</i>		
Total Bearing Load	=	4,239 lbs
...resultant ecc.	=	14.56 in
Soil Pressure @ Toe	=	1,236 psf OK
Soil Pressure @ Heel	=	0 psf OK
Allowable	=	2,000 psf
<i>Soil Pressure Less Than Allowable</i>		
ACI Factored @ Toe	=	1,483 psf
ACI Factored @ Heel	=	0 psf
Footing Shear @ Toe	=	29.3 psi OK
Footing Shear @ Heel	=	16.7 psi OK
Allowable	=	75.0 psi

#### Sliding Calcs Slab Resists All Sliding !

Lateral Sliding Force	=	3,008.0 lbs
less 100% Passive Force	=	- 382.8 lbs
less 100% Friction Force	=	- 1,480.0 lbs
Added Force Req'd	=	1,141.6 lbs NG
...for 1.5 : 1 Stability	=	2,645.6 lbs NG

#### Load Factors

Dead Load	1.200
Live Load	1.600
Earth, H	1.600
Wind, W	1.600
Seismic, E	1.000

### Stem Construction

#### Design Height Above Ftg

Wall Material Above "H"	=	Concrete
Thickness	=	10.00 in
Rebar Size	=	# 5
Rebar Spacing	=	12.00 in
Rebar Placed at	=	Center

#### Design Data

fb/FB + fa/Fa	=	0.686	0.660
Total Force @ Section	lbs =	1,921.0	4,064.8
Moment....Actual	ft-l =	4,437.5	13,735.0
Moment....Allowable	ft-l =	6,464.7	20,802.0
Shear.....Actual	psi =	32.0	41.4
Shear.....Allowable	psi =	75.0	75.0
Wall Weight	psf =	125.0	125.0
Rebar Depth 'd'	in =	5.00	8.19
Lap splice if above	in =	23.40	23.40
Lap splice if below	in =	23.40	4.02
Hook embed into footing	in =	23.40	4.02

#### Concrete Data

f'c	psi =	2,500.0	2,500.0
Fy	psi =	20,000.0	20,000.0

#### Top Stem

#### 2nd

Stem OK	Stem OK
3.17	0.00
Concrete	Concrete
10.00	10.00
# 5	# 5
12.00	6.00
Center	Edge
0.686	0.660
1,921.0	4,064.8
4,437.5	13,735.0
6,464.7	20,802.0
32.0	41.4
75.0	75.0
125.0	125.0
5.00	8.19
23.40	23.40
23.40	4.02
23.40	4.02
2,500.0	2,500.0
20,000.0	20,000.0

Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:13PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: 10' landscape wall - west of garage - 9/S3.2

### Footing Dimensions & Strengths

Toe Width	=	5.00	ft
Heel Width	=	2.00	
Total Footing Width	=	7.00	
Footing Thickness	=	12.00	in
Key Width	=	0.00	in
Key Depth	=	0.00	in
Key Distance from Toe	=	0.00	ft
$f_c$	=	2,500	psi
$F_y$	=	60,000	psi
Footing Concrete Density	=	150.00	pcf
Min. As %	=	0.0018	
Cover @ Top	=	2.00	
@ Btm.	=	3.00	in

### Footing Design Results

	Toe	Heel
Factored Pressure	= 1,483	0 psf
$\mu_u$ : Upward	= 14,036	0 ft-lb
$\mu_u$ : Downward	= 3,850	1,112 ft-lb
$\mu_u$ : Design	= 10,186	1,112 ft-lb
Actual 1-Way Shear	= 29.25	16.73 psi
Allow 1-Way Shear	= 75.00	75.00 psi
Toe Reinforcing	= # 5 @ 6.00 in	
Heel Reinforcing	= None Spec'd	
Key Reinforcing	= None Spec'd	


#### Other Acceptable Sizes & Spacings


Toe: #4@ 7.25 in, #5@ 11.00 in, #6@ 15.75 in, #7@ 21.25 in, #8@ 28.00 in, #9@ 35  
 Heel: Not req'd,  $\mu_u < S * Fr$   
 Key: No key defined

### Summary of Overturning & Resisting Forces & Moments

Item	.....OVERTURNING.....			.....RESISTING.....			
	Force lbs	Distance ft	Moment ft-lb	Force lbs	Distance ft	Moment ft-lb	
Heel Active Pressure	= 3,080.3	3.70	11,396.9	Soil Over Heel	= 1,414.0	6.42	9,073.2
Surcharge over Heel	=			Sloped Soil Over Heel	=		
Toe Active Pressure	= -44.4	0.44	-19.8	Surcharge Over Heel	=		
Surcharge Over Toe	= -27.8	0.67	-18.5	Adjacent Footing Load	=		
Adjacent Footing Load	=			Axial Dead Load on Stem	=		
Added Lateral Load	=			* Axial Live Load on Stem	=		
Load @ Stem Above Soil	=			Soil Over Toe	= 200.0	2.50	500.0
				Surcharge Over Toe	= 250.0	2.50	625.0
				Stem Weight(s)	= 1,325.0	5.42	7,177.1
				Earth @ Stem Transitions	=		
				Footing Weight	= 1,050.0	3.50	3,675.0
				Key Weight	=		
				Vert. Component	=		
<b>Total</b>	= 3,008.0	<b>O.T.M.</b>	= 11,358.7	<b>Total</b>	= 4,239.0	<b>R.M.</b>	= 21,050.3
<b>Resisting/Overturning Ratio</b>		=	<b>1.85</b>				
Vertical Loads used for Soil Pressure	=	4,239.0	lbs				

\* Axial live load NOT included in total displayed, or used for overturning resistance, but is included for soil pressure calculation.





Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:12PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: 10' landscape wall - west of garage - 9/S3.2

Calculations per ACI 318-11, ACI 530-11, IBC 2012,  
 CBC 2013, ASCE 7-10

### Criteria

Retained Height = 10.10 ft  
 Wall height above soil = 0.50 ft  
 Slope Behind Wall = 0.00 : 1  
 Height of Soil over Toe = 4.00 in  
 Water height over heel = 0.0 ft  
 Vertical component of active  
 Lateral soil pressure options:  
 NOT USED for Soil Pressure.  
 NOT USED for Sliding Resistance.  
 NOT USED for Overturning Resistance.

### Soil Data

Allow Soil Bearing = 2,000.0 psf  
 Equivalent Fluid Pressure Method  
 Heel Active Pressure = 50.0 psf/ft  
 Toe Active Pressure = 50.0 psf/ft  
 Passive Pressure = 250.0 psf/ft  
 Soil Density, Heel = 120.00 pcf  
 Soil Density, Toe = 120.00 pcf  
 Friction Coeff btwn Ftg & Soil = 0.350  
 Soil height to ignore  
 for passive pressure = 0.00 in

### Surcharge Loads

Surcharge Over Heel = 0.0 psf  
 Used To Resist Sliding & Overturning  
 Surcharge Over Toe = 50.0 psf  
 Used for Sliding & Overturning

### Axial Load Applied to Stem

Axial Dead Load = 0.0 lbs  
 Axial Live Load = 0.0 lbs  
 Axial Load Eccentricity = 0.0 in

### Lateral Load Applied to Stem

Lateral Load = 80.8 plf  
 ...Height to Top = 10.10 ft  
 ...Height to Bottom = 0.00 ft

Wind on Exposed Stem = 0.0 psf

### Adjacent Footing Load

Adjacent Footing Load = 0.0 lbs  
 Footing Width = 0.00 ft  
 Eccentricity = 0.00 in  
 Wall to Ftg CL Dist = 0.00 ft  
 Footing Type = Line Load  
 Base Above/Below Soil = 0.0 ft  
 at Back of Wall  
 Poisson's Ratio = 0.300

### Design Summary

#### Wall Stability Ratios

Overturning = 1.29 Ratio < 1.5!  
 Sliding = 0.49 UNSTABLE!  
*Slab Resists All Sliding!*  
 Total Bearing Load = 4,239 lbs  
 ...resultant ecc. = 28.54 in  
 Soil Pressure @ Toe = 2,520 psf NG  
 Soil Pressure @ Heel = 0 psf OK  
 Allowable = 2,000 psf  
*Soil Pressure Exceeds Allowable!*  
 ACI Factored @ Toe = 3,024 psf  
 ACI Factored @ Heel = 0 psf  
 Footing Shear @ Toe = 36.2 psi OK  
 Footing Shear @ Heel = 16.7 psi OK  
 Allowable = 75.0 psi

#### Sliding Calcs Slab Resists All Sliding!

Lateral Sliding Force = 3,824.1 lbs  
 less 100% Passive Force = - 382.8 lbs  
 less 100% Friction Force = - 1,480.0 lbs  
 Added Force Req'd = 1,957.6 lbs NG  
 ...for 1.5 : 1 Stability = 3,869.7 lbs NG

#### Load Factors

Dead Load = 1.200  
 Live Load = 1.600  
 Earth, H = 1.600  
 Wind, W = 1.600  
 Seismic, E = 1.000

### Stem Construction

#### Design Height Above Ftg

Wall Material Above "Ht" = Concrete  
 Thickness = 10.00 in  
 Rebar Size = # 5  
 Rebar Spacing = 12.00 in  
 Rebar Placed at = Center

#### Design Data

	Top Stem	2nd
fb/FB + fa/Fa	0.987	0.858
Total Force @ Section	lbs = 2,480.9	4,880.9
Moment....Actual	ft-l = 6,377.7	17,856.2
Moment....Allowable	ft-l = 6,464.7	20,802.0
Shear.....Actual	psi = 46.9	54.7
Shear.....Allowable	psi = 75.0	75.0
Wall Weight	psf = 125.0	125.0
Rebar Depth 'd'	in = 5.00	8.19
Lap splice if above	in = 23.40	23.40
Lap splice if below	in = 23.40	5.33
Hook embed into footing	in = 23.40	5.33

#### Concrete Data

	Top Stem	2nd
f'c	psi = 2,500.0	2,500.0
Fy	psi = 20,000.0	20,000.0



Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:12PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: 10' landscape wall - west of garage - 9/S3.2

### Footing Dimensions & Strengths

Toe Width	=	5.00	ft
Heel Width	=	2.00	
Total Footing Width	=	7.00	
Footing Thickness	=	12.00	in
Key Width	=	0.00	in
Key Depth	=	0.00	in
Key Distance from Toe	=	0.00	ft
$f_c$	=	2,500	psi
$F_y$	=	60,000	psi
Footing Concrete Density	=	150.00	pcf
Min. As %	=	0.0018	
Cover @ Top	=	2.00	
@ Btm.	=	3.00	in

### Footing Design Results

	Toe	Heel
Factored Pressure	= 3,024	0 psf
$\mu_u$ : Upward	= 0	0 ft-lb
$\mu_u$ : Downward	= 0	1,112 ft-lb
$\mu_u$ : Design	= 17,856	1,112 ft-lb
Actual 1-Way Shear	= 36.24	16.73 psi
Allow 1-Way Shear	= 75.00	75.00 psi
Toe Reinforcing	= # 5 @ 6.00 in	
Heel Reinforcing	= None Spec'd	
Key Reinforcing	= None Spec'd	


#### Other Acceptable Sizes & Spacings


Toe: #4@ 5.00 in, #5@ 7.50 in, #6@ 10.75 in, #7@ 14.50 in, #8@ 19.00 in, #9@ 24.  
 Heel: Not req'd,  $\mu_u < S * Fr$   
 Key: No key defined

### Summary of Overturning & Resisting Forces & Moments

Item	.....OVERTURNING.....			.....RESISTING.....			
	Force lbs	Distance ft	Moment ft-lb	Force lbs	Distance ft	Moment ft-lb	
Heel Active Pressure	= 3,080.3	3.70	11,396.9	Soil Over Heel	= 1,414.0	6.42	9,073.2
Surcharge over Heel	=			Sloped Soil Over Heel	=		
Toe Active Pressure	= -44.4	0.44	-19.8	Surcharge Over Heel	=		
Surcharge Over Toe	= -27.8	0.67	-18.5	Adjacent Footing Load	=		
Adjacent Footing Load	=			Axial Dead Load on Stem	=		
Added Lateral Load	= 816.1	6.05	4,937.3	* Axial Live Load on Stem	=		
Load @ Stem Above Soil	=			Soil Over Toe	= 200.0	2.50	500.0
				Surcharge Over Toe	= 250.0	2.50	625.0
				Stem Weight(s)	= 1,325.0	5.42	7,177.1
				Earth @ Stem Transitions	=		
				Footing Weight	= 1,050.0	3.50	3,675.0
				Key Weight	=		
				Vert. Component	=		
<b>Total</b>	= 3,824.1	<b>O.T.M.</b>	= 16,295.9	<b>Total</b>	= 4,239.0 lbs	<b>R.M.</b>	= 21,050.3
<b>Resisting/Overturning Ratio</b>		=	<b>1.29</b>				
Vertical Loads used for Soil Pressure	=	4,239.0	lbs				

\* Axial live load NOT included in total displayed, or used for overturning resistance, but is included for soil pressure calculation.





Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:19PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: 8' retaining wall - grid 1 - 5/S3.3

### Criteria

Retained Height	=	8.30 ft
Wall height above soil	=	0.50 ft
Slope Behind Wall	=	0.00 : 1
Height of Soil over Toe	=	4.00 in
Water height over heel	=	0.0 ft
Vertical component of active Lateral soil pressure options:		
NOT USED for Soil Pressure.		
NOT USED for Sliding Resistance.		
NOT USED for Overturning Resistance.		

### Soil Data

Allow Soil Bearing	=	2,000.0 psf
Equivalent Fluid Pressure Method		
Heel Active Pressure	=	50.0 psf/ft
Toe Active Pressure	=	50.0 psf/ft
Passive Pressure	=	250.0 psf/ft
Soil Density, Heel	=	120.00 pcf
Soil Density, Toe	=	120.00 pcf
Friction Coeff btwn Ftg & Soil	=	0.350
Soil height to ignore for passive pressure	=	0.00 in

Calculations per ACI 318-11, ACI 530-11, IBC 2012,  
 CBC 2013, ASCE 7-10

maximum 2H:1V slope behind wall.

### Surcharge Loads

Surcharge Over Heel	=	0.0 psf
Used To Resist Sliding & Overturning		
Surcharge Over Toe	=	50.0 psf
Used for Sliding & Overturning		

### Axial Load Applied to Stem

Axial Dead Load	=	506.0 lbs
Axial Live Load	=	661.0 lbs
Axial Load Eccentricity	=	0.0 in

### Lateral Load Applied to Stem

Lateral Load	=	0.0 plf
...Height to Top	=	8.30 ft
...Height to Bottom	=	0.00 ft

### Adjacent Footing Load

Adjacent Footing Load	=	0.0 lbs
Footing Width	=	0.00 ft
Eccentricity	=	0.00 in
Wall to Ftg CL Dist	=	0.00 ft
Footing Type		Line Load
Base Above/Below Soil at Back of Wall	=	0.0 ft
Poisson's Ratio	=	0.300

### Design Summary

#### Wall Stability Ratios

Overturning	=	1.70 OK
Sliding	=	1.51 OK
Total Bearing Load	=	4,477 lbs
...resultant ecc.	=	10.23 in
Soil Pressure @ Toe	=	1,607 psf OK
Soil Pressure @ Heel	=	46 psf OK
Allowable	=	2,000 psf
Soil Pressure Less Than Allowable		
ACI Factored @ Toe	=	2,023 psf
ACI Factored @ Heel	=	58 psf
Footing Shear @ Toe	=	23.1 psi OK
Footing Shear @ Heel	=	3.0 psi OK
Allowable	=	75.0 psi
<b>Sliding Calcs</b> (Vertical Component NOT Used)		
Lateral Sliding Force	=	2,215.9 lbs
less 100% Passive Force	= -	3,336.8 lbs
less 0 % Friction Force	= -	0.0 lbs
Added Force Req'd	=	0.0 lbs OK
...for 1.5 : 1 Stability	=	0.0 lbs OK

### Stem Construction

#### Design Height Above Ftg

Design Height Above Ftg	ft =	2.75	Stem OK
Wall Material Above "Ht"	=	Concrete	Concrete
Thickness	in =	8.00	8.00
Rebar Size	=	# 4	# 4
Rebar Spacing	in =	12.00	6.00
Rebar Placed at	=	Center	Edge

#### Design Data

fb/FB + fa/Fa	=	0.673	0.733
Total Force @ Section	lbs =	1,232.1	2,740.0
Moment....Actual	ft-l =	2,279.4	7,621.5
Moment....Allowable	ft-l =	3,387.6	10,400.4
Shear.....Actual	psi =	25.7	36.5
Shear.....Allowable	psi =	75.0	75.0
Wall Weight	psf =	100.0	100.0
Rebar Depth 'd'	in =	4.00	6.25
Lap splice if above	in =	18.72	18.72
Lap splice if below	in =	18.72	8.40
Hook embed into footing	in =	18.72	8.40

#### Concrete Data

f'c	psi =	2,500.0	2,500.0
Fy	psi =	24,000.0	20,000.0

### Load Factors

Dead Load	1.200
Live Load	1.600
Earth, H	1.600
Wind, W	1.600
Seismic, E	1.000

Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:19PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: 8' retaining wall - grid 1 - 5/S3.3

### Footing Dimensions & Strengths

Toe Width	=	4.42	ft
Heel Width	=	1.00	
Total Footing Width	=	5.42	
Footing Thickness	=	16.00	in
Key Width	=	16.00	in
Key Depth	=	37.00	in
Key Distance from Toe	=	0.00	ft
$f_c$	=	2,500	psi
$F_y$	=	60,000	psi
Footing Concrete Density	=	150.00	pcf
Min. As %	=	0.0018	
Cover @ Top	=	2.00	@ Btm. = 3.00 in

### Footing Design Results

	Toe	Heel
Factored Pressure	= 2,023	58 psf
$\mu'$ : Upward	= 0	0 ft-lb
$\mu'$ : Downward	= 0	80 ft-lb
$\mu$ : Design	= 7,621	80 ft-lb
Actual 1-Way Shear	= 23.11	2.95 psi
Allow 1-Way Shear	= 75.00	75.00 psi
Toe Reinforcing	= # 4 @ 6.00 in	
Heel Reinforcing	= None Spec'd	
Key Reinforcing	= # 4 @ 8.00 in	


#### Other Acceptable Sizes & Spacings

Toe: #4@ 9.00 in, #5@ 14.00 in, #6@ 19.75 in, #7@ 26.75 in, #8@ 35.25 in, #9@ 44  
 Heel: Not req'd,  $\mu < S * Fr$   
 Key: #4@ 8.75 in, #5@ 13.25 in, #6@ 19.00 in, #7@ 25.75 in,

### Summary of Overturning & Resisting Forces & Moments

Item	.....OVERTURNING.....			.....RESISTING.....			
	Force lbs	Distance ft	Moment ft-lb	Force lbs	Distance ft	Moment ft-lb	
Heel Active Pressure	= 2,320.0	3.21	7,449.9	Soil Over Heel	= 332.0	5.25	1,743.1
Surcharge over Heel	=			Sloped Soil Over Heel	=		
Toe Active Pressure	= -69.4	0.56	-38.6	Surcharge Over Heel	=		
Surcharge Over Toe	= -34.7	0.83	-28.9	Adjacent Footing Load	=		
Adjacent Footing Load	=			Axial Dead Load on Stem	= 506.0	4.75	2,403.7
Added Lateral Load	=			* Axial Live Load on Stem	= 661.0	4.75	3,140.0
Load @ Stem Above Soil	=			Soil Over Toe	= 176.7	2.21	390.2
				Surcharge Over Toe	= 220.9	2.21	487.7
				Stem Weight(s)	= 880.0	4.75	4,180.3
				Earth @ Stem Transitions	=		
<b>Total</b>	= 2,215.9	<b>O.T.M.</b>	= 7,382.4	Footing Weight	= 1,083.4	2.71	2,934.4
<b>Resisting/Overturning Ratio</b>		=	<b>1.70</b>	Key Weight	= 616.7	0.67	411.1
Vertical Loads used for Soil Pressure	=	4,476.6	lbs	Vert. Component	=		
				<b>Total</b>	= 3,815.6	<b>lbs R.M.</b>	= 12,550.5

\* Axial live load NOT included in total displayed, or used for overturning resistance, but is included for soil pressure calculation.




$$R_1 = \frac{42.58}{49.5} (4.477^*) = 3.93^*/ft.$$

$$S_1 = 20.0w / 3.93^*/ft. = \underline{5'-1" oc} \text{ (4" } \phi \text{ PILES)}$$

$$R_2 = \frac{33.81}{46.5} (4.477^*) = 3.12^*/ft.$$

$$S_2 = 20.0w / 3.12^*/ft. = \underline{6'-4" oc} \text{ (4" } \phi \text{ PILES)}$$



Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:18PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: 8' retaining wall - grid 1 - 5/S3.3

### Criteria

Retained Height = 8.30 ft  
 Wall height above soil = 0.50 ft  
 Slope Behind Wall = 0.00 : 1  
 Height of Soil over Toe = 4.00 in  
 Water height over heel = 0.0 ft  
 Vertical component of active  
 Lateral soil pressure options:  
 NOT USED for Soil Pressure.  
 NOT USED for Sliding Resistance.  
 NOT USED for Overturning Resistance.

### Soil Data

Allow Soil Bearing = 2,000.0 psf  
 Equivalent Fluid Pressure Method  
 Heel Active Pressure = 50.0 psf/ft  
 Toe Active Pressure = 50.0 psf/ft  
 Passive Pressure = 250.0 psf/ft  
 Soil Density, Heel = 120.00 pcf  
 Soil Density, Toe = 120.00 pcf  
 Friction Coeff btwn Ftg & Soil = 0.350  
 Soil height to ignore  
 for passive pressure = 0.00 in

Calculations per ACI 318-11, ACI 530-11, IBC 2012,  
 CBC 2013, ASCE 7-10

### Surcharge Loads

Surcharge Over Heel = 0.0 psf  
 Used To Resist Sliding & Overturning  
 Surcharge Over Toe = 50.0 psf  
 Used for Sliding & Overturning

### Axial Load Applied to Stem

Axial Dead Load = 506.0 lbs  
 Axial Live Load = 661.0 lbs  
 Axial Load Eccentricity = 0.0 in

### Design Summary

#### Wall Stability Ratios

Overturning = 1.21 Ratio < 1.5!  
 Sliding = 1.21 Ratio < 1.5!  
 Total Bearing Load = 4.477 lbs  
 ...resultant ecc. = 18.33 in  
 Soil Pressure @ Toe = 2,527 psf NG  
 Soil Pressure @ Heel = 0 psf OK  
 Allowable = 2,000 psf  
*Soil Pressure Exceeds Allowable!*  
 ACI Factored @ Toe = 3,182 psf  
 ACI Factored @ Heel = 0 psf  
 Footing Shear @ Toe = 28.9 psi OK  
 Footing Shear @ Heel = 3.0 psi OK  
 Allowable = 75.0 psi  
**Sliding Calcs** (Vertical Component NOT Used)  
 Lateral Sliding Force = 2,767.0 lbs  
 less 100% Passive Force = - 3,336.8 lbs  
 less 0 % Friction Force = - 0.0 lbs  
 Added Force Req'd = 0.0 lbs OK  
 ...for 1.5 : 1 Stability = 813.7 lbs NG

#### Load Factors

Dead Load 1.200  
 Live Load 1.600  
 Earth, H 1.600  
 Wind, W 1.600  
 Seismic, E 1.000

### Lateral Load Applied to Stem

Lateral Load = 66.4 plf  
 ...Height to Top = 8.30 ft  
 ...Height to Bottom = 0.00 ft

Wind on Exposed Stem = 0.0 psf

### Stem Construction

#### Design Height Above Ftg

ft = 2.75  
 Wall Material Above "Ht" = Concrete  
 Thickness = 8.00 in  
 Rebar Size = # 4  
 Rebar Spacing = 12.00 in  
 Rebar Placed at = Center

#### Design Data

	Top Stem	2nd
fb/FB + fa/Fa	0.975	0.953
Total Force @ Section	lbs = 1,600.6	3,291.2
Moment....Actual	ft-l = 3,302.0	9,908.6
Moment....Allowable	ft-l = 3,387.6	10,400.4
Shear.....Actual	psi = 38.0	48.3
Shear.....Allowable	psi = 75.0	75.0
Wall Weight	psf = 100.0	100.0
Rebar Depth 'd'	in = 4.00	6.25
Lap splice if above	in = 18.72	18.72
Lap splice if below	in = 18.72	8.40
Hook embed into footing	in = 18.72	8.40

#### Concrete Data

f'c	psi = 2,500.0	2,500.0
Fy	psi = 24,000.0	20,000.0

### Adjacent Footing Load

Adjacent Footing Load = 0.0 lbs  
 Footing Width = 0.00 ft  
 Eccentricity = 0.00 in  
 Wall to Ftg CL Dist = 0.00 ft  
 Footing Type Line Load  
 Base Above/Below Soil = 0.0 ft  
 at Back of Wall  
 Poisson's Ratio = 0.300



Title Block Line 1  
 You can change this area  
 using the "Settings" menu item  
 and then using the "Printing &  
 Title Block" selection.  
 Title Block Line 6

Project Title:  
 Engineer:  
 Project Descr:

Project ID:

Printed: 27 AUG 2022, 1:18PM

## Cantilevered Retaining Wall

File = C:\ASE\Projects\MOUNGE~1\CALCUL~1\MOUNGE~1.EC6  
 ENERCALC, INC. 1983-2015, Build:6.15.7.30, Ver:6.15.12.31

Lic. #: KW-06009341

Licensee: Annee Structural Engineering LLC

Description: 8' retaining wall - grid 1 - 5/S3.3

### Footing Dimensions & Strengths

Toe Width	=	4.42	ft
Heel Width	=	1.00	
Total Footing Width	=	5.42	
Footing Thickness	=	16.00	in
Key Width	=	16.00	in
Key Depth	=	37.00	in
Key Distance from Toe	=	0.00	ft
$f_c$	=	2,500	psi
$F_y$	=	60,000	psi
Footing Concrete Density	=	150.00	pcf
Min. As %	=	0.0018	
Cover @ Top	=	2.00	@ Btm. = 3.00 in

### Footing Design Results

		<u>Toe</u>	<u>Heel</u>
Factored Pressure	=	3,182	0 psf
$\mu_u$ : Upward	=	0	0 ft-lb
$\mu_u$ : Downward	=	0	80 ft-lb
$\mu_u$ : Design	=	9,909	80 ft-lb
Actual 1-Way Shear	=	28.85	2.95 psi
Allow 1-Way Shear	=	75.00	75.00 psi
Toe Reinforcing	=	# 4 @ 6.00 in	
Heel Reinforcing	=	None Spec'd	
Key Reinforcing	=	# 4 @ 8.00 in	

#### Other Acceptable Sizes & Spacings

Toe: #4@ 9.00 in, #5@ 14.00 in, #6@ 19.75 in, #7@ 26.75 in, #8@ 35.25 in, #9@ 44  
 Heel: Not req'd,  $\mu_u < S * Fr$   
 Key: #4@ 8.75 in, #5@ 13.25 in, #6@ 19.00 in, #7@ 25.75 in,

### Summary of Overturning & Resisting Forces & Moments

Item	.....OVERTURNING.....			.....RESISTING.....		
	Force lbs	Distance ft	Moment ft-lb	Force lbs	Distance ft	Moment ft-lb
Heel Active Pressure	=	2,320.0	3.21	7,449.9		
Surcharge over Heel	=					
Toe Active Pressure	=	-69.4	0.56	-38.6		
Surcharge Over Toe	=	-34.7	0.83	-28.9		
Adjacent Footing Load	=					
Added Lateral Load	=	551.1	5.48	3,022.0		
Load @ Stem Above Soil	=					
<b>Total</b>	=	<b>2,767.0</b>	<b>O.T.M. =</b>	<b>10,404.3</b>		
<b>Resisting/Overturning Ratio</b>			=	<b>1.21</b>		
Vertical Loads used for Soil Pressure	=		4,476.6	lbs		
Soil Over Heel	=			332.0	5.25	1,743.1
Sloped Soil Over Heel	=					
Surcharge Over Heel	=					
Adjacent Footing Load	=					
Axial Dead Load on Stem	=			506.0	4.75	2,403.7
* Axial Live Load on Stem	=			661.0	4.75	3,140.0
Soil Over Toe	=			176.7	2.21	390.2
Surcharge Over Toe	=			220.9	2.21	487.7
Stem Weight(s)	=			880.0	4.75	4,180.3
Earth @ Stem Transitions	=					
Footing Weight	=			1,083.4	2.71	2,934.4
Key Weight	=			616.7	0.67	411.1
Vert. Component	=					
<b>Total</b>				<b>3,815.6</b>	<b>lbs R.M. =</b>	<b>12,550.5</b>

\* Axial live load NOT included in total displayed, or used for overturning resistance, but is included for soil pressure calculation.