CITY OF MERCER ISLAND

Community Planning & Development 9611 SE 36TH STREET | MERCER ISLAND, WA 98040 PHONE: 206.275.7605 | www.mercerisland.gov



INSPECTION	REQUEST

	MyBuildingPermit.co
_	

voicemail: (206) 275-7730

NOTE: ALL RECORDS AND DRAWINGS ARE SUBJECT TO PUBLIC DISCLOSURE AS REQUIRED BY RCW 42.56

CONTACT INFORMATION:				
Applicant is to complete the following information.				
Applicant Contact information prior to permit issuance:	Applicant Contact information post permit issuance:			
Name: ROBIN QUINN, BOARD AND VELLUM	Name: ROBIN QUINN, BOARD AND VELLUM			
Address: 115 15TH AVE E STE 100, SEATTLE WA 98112	Address: 115 15TH AVE E STE 100, SEATTLE WA 98112			
Phone: (206) 707-8895	Phone: (206) 707-8895			
Email: robin@boardandvellum.com	Email: robin@boardandvellum.com			

	d the rene	ort :	shall be submitted to the City Building Inspector prior to the Ci
Inspection. Note: Inspection by the City Inspector is require	d in additi		to the Special Inspection or Structural Observation indicated
below. Do not cover or conceal any work prior to the City in	spection.		
STRUCTURAL OBSERVATION BY ENGINEER OF RECORD			
Engineer of Record: General Conformance to Construction Documents	_ Compan		Other:Phone:
-		ш	Other:
SOILS / GEOTECHNICAL: Special Inspector:	Compan		Phone:
Erosion control measures			Subsurface drainage placement
Shoring installation and monitoring			Verify fill material and compaction
Observe and monitor excavation			Rockery installation
☐ Verification of soil bearing ☐ Other:		H	Pile placement (auger cast/driven pile) Other:
REINFORCED CONCRETE:		_	
	_ Compan	ıv:	Phone:
Concrete strength			Retaining wall construction
Reinforcing steel and concrete placement			Prestressed / Precast construction
Shotcrete placement Other:			Other:
_		۷	one.
STRUCTURAL STEEL: (ASC 200, Chapter N) Special Inspector:	_ Compan		Phone:
☐ Fabrication and shop welds			Moment Frame construction
Structural steel erection, field welds and bolting			Other:
Other:			Other:
STRUCTURAL MASONRY:			
Special Inspector:			Phone:
Mortar strength			Glass unit masonry installation
☐ Masonry unit strength ☐ Other:		H	Wall panel and veneer installation Other:
Other:			Other:
WOOD:			
Special Inspector /			
	_ Compan		Phone:
Lateral resisting system construction Other:			High strength diaphragm construction Other:
OTHER SPECIAL INSPECTIONS:		_	Silici
Special Inspector:	Compan	ıv:	Phone:
☐ Epoxy grout installations			Stucco installation
Expansion anchor installations			Infiltration System
Other post installed anchors Alternative construction methods:		밈	Exterior Insulation Finish System (EIFS) installation
Alternative construction methods: Alternative construction materials:		H	Other:
DEFERRED SUBMITTALS:			
	shop drav	vin	gs for submittal to the City for review and approval prior to it
fabrication / construction.			
Connector plate wood trusses			Post tension layout
		H	Exterior cladding Window wall / curtain wall construction
Precast concrete elements		Ħ	Other:
Other:			Other:
Indicate where the following information is located in the c	frawing se	t. A	Iternatively, incorporate or include the Residential Energy Co
Prescriptive Compliance (RECPC) Form into the drawing set			
Sheet			
✓ Building envelope: ws/c Table 402.1.1 G1.0	1	◩	Air Leakage Testing. In: Section 8402.4.1.2 IN Amendments
(include U-factors, insulation and moisture control)	1		Provide air leakage test report verifying air leakage rate
Whole house ventilation: NO Section MESON MA APPRING G1.0 (include ventilation option and duct sizing if applicable)		ø	does not to exceed 5 air changes per hour. Duct Leakage Testing, wascewaszz
✓ Energy Credit Information: wsccrose-assz	1	V	Postconstruction Test. wsrc mea.2.2.1
(include specific, written requirements) RECPC Form Information: G1.0		V	Rough-in Test. wssc #653.223
✓ RECPC Form Information: G1.0 (if incorporated within drawing set)			
(if incorporated within drawing set) http://www.mersegov.org/files/20128esidentia/Deorg/Calcform.pdf			

Construction of the project shall be from approved pions only. No deviation from the approved project plans is allowed without prior secretarian the forty of Metera thinds. Approved pions must be tept on site and minimal and on applications, including: A less of the control of the prior of the start of any site work and prior of the start of any site work and prior of the start of any site work and prior of the prior of the start of any site work and prior of the start of any site work and prior of the start of any site work and prior of the start of any site work and prior of the start of any site work and prior of the start of any site work and prior of the start of any site work and prior of the start of the prior of th					
Refer to "Condition or Permit Approved plans must be kept on site and minimalised in good condition. Refer to "Condition or Permit Approved provided at permit Source for required construction uses and repulsitions, including	PROJECT ALERTS:				
Refer to "Condition or Permit Approved plans must be kept on site and minimalised in good condition. Refer to "Condition or Permit Approved provided at permit Source for required construction uses and repulsitions, including	Construction of the project shall be from approved plans of	nly. No deviation from the approved project plans is allowed without prior			
- Step Considerations - Hours of Work Considerations - Hours of Work Considerations - Hours of Work Considerations - Water Service Requirements - Tree	approval from the City of Mercer Island. Approved plans m	ust be kept on site and maintained in good condition.			
- Step Considerations - Hours of Work Considerations - Hours of Work Considerations - Hours of Work Considerations - Water Service Requirements - Tree	✓ Refer to "Conditions of Permit Approval" provided at	permit issuance for required construction rules and regulations, including:			
- Hours of Work - Construction Vehicle Parking Restrictions - Sover Requirements - Sover Requ	Site Considerations ROW restrictions Additional Fire Code Requirements				
- Construction Vehicle Parking Restrictions *Outs et Sevice Requirements *Outs et Sevice Requirements *Tree Parketion *Tr	Hours of Work Drain	nage Requirements • Planning Requirements			
*Alsos Road Requirements	 Construction Vehicle Parking Restrictions Sewe 	er Requirements • Noise Abatement Certification			
Refer to *Preconstruction Meeting Checkist* provided at the precovation meeting for development related requirements. Interpretation of the provided such minimum of high numbers visible from the stream that be intailled to the place and inspected project diversing. All crassion control is to be in place and inspected project diversing. All crassion control is to be in place and inspected project diversing. All crassion control is to be in place and inspected project diversing. All crassion control is to be in place and inspected project diversing shall be installed at tree dipline prior to start of any site work and many and project projects and shall be installed at tree dipline prior to start of any site work and many and project projects appears to be within a protected eagle nest area. Contact federal fish and Wildlife at (20) 534-9304 or visit their vessible in this/place but within a protected eagle nest area. Contact federal fish and Wildlife at (20) 534-9304 or visit their vessible in this/place in the project spears to be within a protected eagle nest area. Contact federal fish and Wildlife at (20) 534-9304 or visit their vessible in this/place in the project spears to be within a protected eagle nest area. Contact federal fish and Wildlife at (20) 534-9304 or visit their vessible in this/place in the project spears to be within a protected eagle nest area. Contact federal fish and Wildlife at (20) 534-9304 or visit their vessible in this/place in the project spears to be within a protected eagle nest area. Contact federal fish and Wildlife at (20) 534-9304 or visit their vessible in this place is a project spears to be contact federal fish and wildlife at (20) 534-9304 or visit their vessible in the contact federal fish and wildlife at (20) 534-9304 or visit their vessible in the contact federal fish and wildlife at (20) 534-9304 or visit their vessible in the contact federal fish and wildlife at (20) 534-9304 or visit their vessible in the contact federal fish and wildlife at (20) 534-9304 or v					
A City of New Process and Supress Livense in required for all subcontractors. Call (206) 275-7783 for more information. INTERPOTECTION REQUERED TO SUPPLY CONTRACTORS AND ADDRESS AND ADD	Refer to "Preconstruction Meeting Checklist" provider	d at the preconstruction meeting for development related requirements.			
A City of New Process and Supress Livense in required for all subcontractors. Call (206) 275-7783 for more information. INTERPOTECTION REQUERED TO SUPPLY CONTRACTORS AND ADDRESS AND ADD	▼ Temporary site address with minimum 6" high number	ers visible from the street must be installed.			
A City of New Process and Supress Livense in required for all subcontractors. Call (206) 275-7783 for more information. INTERPOTECTION REQUERED TO SUPPLY CONTRACTORS AND ADDRESS AND ADD	☑ Erosion control measures must be as shown on appro	oved project drawings. All erosion control is to be in place and inspected			
### PROTECTION REQUIREMENTS: The protection as shown on approved drawings that bis installed at tree dripline prior to start of any site work and most remain in place throughout the project.					
### PROTECTION REQUIREMENTS: The protection as shown on approved drawings that bis installed at tree dripline prior to start of any site work and most remain in place throughout the project.	✓ A City of Mercer Island Business License is required fo	or all subcontractors. Call (206) 275-7783 for more information.			
The protection as shown on approved drowings that be installed at tree dripline prior to start of any site work and most remains in piece throughout the project.					
must remain in place throughout the project. Replacement trees must be a minimum of six feet tail at installation. They must be planted and approved prior to final inspection. This project appears to be within a protected eagle next area. Contact Feetral Fish and Windfield at (560) \$34-9300 or visit their website is thingly-flowed fore projected place. The project appears to be within a protected eagle next area. Contact Feetral Fish and Windfield and Stage parts Permitted and project appears to be within a protected eagle next area. Contact Feetral Fish and Windfield and Stage parts Permitted and Project appears to the within a protected eagle next area. Contact Feetral Fish and Windfield and Stage parts Permitted and Project appears to the second Project Pr					
No trees shall be cut without a city of Mercer Island tree permit. Replacement rese must be an information. Replacement in straight and approved prior to final inspection. For this project, IyA_ Trees. are authorized to be removed and replaced with IyA_ Trees.	▼ Tree protection as shown on approved drawings shall	be installed at tree dripline prior to start of any site work and			
Replacement trees must be a minimum of six feet tail at installation. They must be glamted and approved prior to final inspection. To stronger, [NA] I trees are authorized to be removed and replaced with [NA] I trees which a project appears to be within a protectoric eagle nest area. Contact Federal Fish and Wildlife at (360) \$34-930d or visit their website at http://www.mer.org/public/loades	must remain in place throughout the project.				
For this project, IN/A rees. are authorized to be removed and replaced with (NA rees.	M No trees shall be cut without a City of Mercer island to	ree permit.			
This project appears to be within a protected eagle nest area. Contact Federal Fish and Wildlife at (\$60) \$34-9304 or visit their website at http://www.mer.gorp.vorg/Page.so/NavD-2514 Fire Sprinkler	Replacement trees must be a minimum of six feet tall	at installation. They must be planted and approved prior to final inspection.			
Water Supply Recourse Size March Size Mar	This project appears to be within a protected earle pe	net area. Contact Endoral Eich and Wildlife at (260) E24 0204 or visit their			
### PROTECTION REQUIREMENTS: Price Sprinder	webrite at http://www.fur.gov/pacific/cagle	escarea. Contact rederal rish and wholite at (500/ 554-5504 of visit their			
Fire Sprinkler	website at http://www.rws.gov/pacinc/eagle				
Fire Sprinkler	FIRE PROTECTION REQUIREMENTS:				
Fire Sprinkler	eparate Permits are required for ALL fire protection systen	ns. For more information, see http://www.mercergov.org/Page.asp?NavID=2614			
PRA 13D Plus		Monitored Household			
Pilus Montroef Sprinkler	NFPA 13D	Fire Alarm per NFPA 72			
NPFA 38	☐ Plus	Monitored Sprinkler			
Other:	NFPA 13R	Water Flow Alarm			
GrCA2 GrCA3 GrCA4	□ NFPA 13	Other:			
FCA2	Approved Fire Code Alternatives:				
FCAZ	FCA1	FCA3			
Fire sprinkler design calculations must be provided prior to determining water supply system requirements. Hire Supply system upgrade required City Installation. Applicant forstallation. Applicant for					
Fire sprinkler design calculations must be provided prior to determining water supply system requirements. Hire Supply system upgrade required City Installation. Applicant forstallation. Applicant for	FCA2	FCA4			
First spinkler design calculations must be provided prior to determining water supply system requirements.					
Fire sprinker design calculations must be provided prior to determining water supply system requirements.	MATER SLIDRI V DECLUREMENTS				
Sate Super requires Water main to notes Water main to notes Water main to notes Water main to notes Water main to note Wa					
Water Supply system upgrade required City Installation. Applicant Installation. Applicant Installation. Required Supply Line Size: W/A Required Meter Size: W/A (water main to mater) (water main to mai	Fire sprinkler design calculations must be provided pr	rior to determining water supply system requirements.			
Carlo Installation. Applicant to mater Water main to house) Water main to house	■ Water Supply system upgrade required				
Required Service Line Size: [MA Required Supply Line Size: [MA Required Meter Size: [MA (water main to meter) (water main to house)	City Installation.				
(water main to moster) (water main to mouse)	Applicant Installation.				
Anadomement of existing service and meter required at main. Pressure reducing valve required if pressure exceeds 80 ps. Reduced pressure backflow assembly (RPRA) required for all lots with waterfront or non-city water supply (private wells or alka trigation). Additional water supply requirements: On site detention system required. On site detention system required. On site infiliation system system required. On site infiliation system system required system require	Required Service Line Size: N/A Required	Supply Line Size: N/A Required Meter Size: N/A			
Pressure reducing valve required if pressure exceeds 80 psi. Reduced pressure backflow assembly (graph required for all lots with waterfront or non-city water supply (private wells or lake irrigation). Additional water supply requirements: Path					
Reduced pressure backfow assembly (RPRA) required for all lots with waterfront or non-city water supply (private wells or at lake irrigator) and distinual water supply (private wells or at lake irrigator) and in the properties of the propertie	Abandonment of existing service and meter required	at main.			
Reduced pressure backfow assembly (RPRA) required for all lots with waterfront or non-city water supply (private wells or at lake irrigator) and distinual water supply (private wells or at lake irrigator) and in the properties of the propertie	Description and union union required if proceurs avenues	90 nci			
Additional water supply requirements: Constitution Constituti	■ Reduced pressure backflow assembly (RPBA) required	for all lots with waterfront or non-city water supply (private wells			
On site detention system required. On site infiltration system required. One site in	or take irrigation).				
Direct discharge into the lake.	Additional water supply requirements:				
Direct discharge into the lake.	DRAINAGE REQUIREMENTS:				
On Stem Mater permit required. Ostorm Water permit perm		C Since distance into the Li			
□ A-built Utility drawings required. □ Connection to public storm drainage conveyance system req.d. □ Collection Full Size dewaigs required. □ Collection Collect	Un site detention system required.	Direct discharge into the lake			
Other: Other: Other:	Un site infiltration system required				
Set Sever requires a backflow preventer when connecting to the lake line or when the elevation of the lowest plumbing fixture is lower than the elevation of the upstream manhole rim or when side sever is shared with one or more properties. Content C					
Side sewer requires a backflow preventer when connecting to the lake line or when the elevation of the lowest plumbling fixture is lower than the elevation of the upstram manhole in or when side sewer is shared with one or more properties. Other New Connection Connect to esisting. Disconnect permit required. Reconnect permit required. New Connection Connection Connection Disconnect permit required. Reconnect permit required.	As-built offitty drawings required.				
Ower than the elevation of the upstream manhole rin or when side sever is shared with one or more properties. Video tape of existing sever regulared (see standard details) Ower connection. Connect to existing. Disconnect permit required. Reconnect permit required. Note: When side sever is to be connected to the lake line you will need to schedule three (3) days in advance with the City of Mercer Island Maintenance Department at (206) 275-7800. PORTONED CODE ALTERNATIVES: October CA1: CA2: CA2:	Full Size drawings required.	Other:			
Ower than the elevation of the upstream manhole rin or when side sever is shared with one or more properties. Video tape of existing sever regulared (see standard details) Ower connection. Connect to existing. Disconnect permit required. Reconnect permit required. Note: When side sever is to be connected to the lake line you will need to schedule three (3) days in advance with the City of Mercer Island Maintenance Department at (206) 275-7800. PORTONED CODE ALTERNATIVES: October CA1: CA2: CA2:	Full Size drawings required.	Other:			
Video tape of existing sever required (see standard details) New connection	Full Size drawings required. SIDE SEWER REQUIREMENTS:	Other:			
New connection. Connect to existing. Disconnect permit required. Reconnect permit required. Other: Note: When side sewer is to be connected to the lake line you will need to schedule three (3) days in advance with the City of Mercer Island Maintenance Department at (266) 275-7800. POPROVED CODE ALTERNATIVES: CA1: CA2: CA3: CA4: CA4: CA4: CA5: CA5: CA	☐ Full Size drawings required. SIDE SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn	Other:			
Other	☐ Full Size drawings required. SIDE SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rir	Other: ecting to the lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties.			
Note: When side sever is to be connected to the lake line you will need to schedule three (3) days in advance with the City of Mercers Island Maintenance Department at (206) 275-7800. **PPROVED CODE ALTERNATIVES:** does alternatives must be inspected. Refer to the inspection Checklist CA1:	☐ Full Size drawings required. SIDE SEWER REQUIREMENTS: SIDE Sewer requires a backflow preventer when connower than the elevation of the upstream manhole ring the table to be standard of the process of the standard of the process of the proces	Other: Other: Other: Other average of the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Retails)			
Mercer Island Maintenance Department at (206) 275-7800. Mercer Island Maintenance Department at (206) 275-7800. CA1:	Full Size drawings required. IDE SEWER REQUIREMENTS: Side sewer requires a backflow preventer when connower than the elevation of the upstream manhole ringle tage tage of existing sewer required (see standard of New connection. Ownect to existine.	Other: Other: Other: Other average of the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Retails)			
CA2:	□ Full Size drawings required. Del SEVVER REQUIREMENTS: Side sever requires a backflow preventer when conn lower than the elevation of the upstream manhole if Video tape of existing sewer required (see standard of New connection. □ Connect to existing.	Other: Other:			
CA1: CA2:	☐ Full Size drawings required. IDE-SEWER REQUIREMIENTS: Side sever requires a backflow preventer when connover than the elevation of the upstream manhole rir Video tape of existing sever required (see standard of one to existing). New connection. Other: Note: When side sewer is to be connected to the lake	Other: ecting to the lake line or when the elevation of the lowest plumbing fixture is nor when side sewer is shared with one or more properties. letails) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of			
CA1: CA2:	☐ Full Size drawings required. IDE-SEWER REQUIREMIENTS: Side sever requires a backflow preventer when connover than the elevation of the upstream manhole rir Video tape of existing sever required (see standard of one to existing). New connection. Other: Note: When side sewer is to be connected to the lake	Other: ecting to the lake line or when the elevation of the lowest plumbing fixture is nor when side sewer is shared with one or more properties. letails) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of			
URVEY REQUIREMENTS me to leaves wave information must be whented when sheeted. uneyor shall verify points chosen for height calculations and opin verification shall be submitted at the time of Gity foundation systems of the property survey may be required to verify seables and in some cases buildings must be surveyed not the lot. The City sessions for right to request an impervious area survey at any time prior to issuance of Certificate of Occupancy. Building height survey,	☐ If ull size drawings required. IDESEWER REQUIREMENTS: IDESEWER REQUIREMENTS: IDESEMBLY REQUIREMENTS: IDESEMBLY REQUIREMENTS: IDESEMBLY REQUIREMENTS: IDESEMBLY REQUIREMENTS: IDESEMBLY REQUIREMENTS: IDESEMBLY RE	Other: Other: Other: Other lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties. Disconnect permit required. Reconnect permit required. Line you will need to schedule three (3) days in advance with the City of 16) 275-7800.			
URVEY REQUIREMENTS me to leaves wave information must be whented when sheeted. uneyor shall verify points chosen for height calculations and opin verification shall be submitted at the time of Gity foundation systems of the property survey may be required to verify seables and in some cases buildings must be surveyed not the lot. The City sessions for right to request an impervious area survey at any time prior to issuance of Certificate of Occupancy. Building height survey,	☐ If ull size drawings required. IDESEWER REQUIREMENTS: IDESEWER REQUIREMENTS: IDESEMBLY REQUIREMENTS: IDESEMBLY REQUIREMENTS: IDESEMBLY REQUIREMENTS: IDESEMBLY REQUIREMENTS: IDESEMBLY REQUIREMENTS: IDESEMBLY RE	Other: Other: Other: Other lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties. Disconnect permit required. Reconnect permit required. Line you will need to schedule three (3) days in advance with the City of 16) 275-7800.			
spection. A property survey may be required to verify setbacks and in some cases buildings must be surveyed onto the lot. The City sessives the right to request an improvisus area survey at any time prior to issuance of Certificate of Cocupancy. Building height survey Phone:	☐ Full Size drawings required. IDDESSEVER FREQUIREVENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream maintole rir Video tape of existing sewer required (see standard of	Other: cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Editals) Disconnect permit required. Reconnect permit required. el line you will need to schedule three (3) days in advance with the City of (6) 275-7800.			
spection. A property survey may be required to verify setbacks and in some cases buildings must be surveyed onto the lot. The City sessives the right to request an improvisus area survey at any time prior to issuance of Certificate of Cocupancy. Building height survey Phone:	☐ Full Size drawings required. IDDESSEVER FREQUIREVENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream maintole rir Video tape of existing sewer required (see standard of	Other: cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Editals) Disconnect permit required. Reconnect permit required. el line you will need to schedule three (3) days in advance with the City of (6) 273-7800.			
spection. A property survey may be required to verify setbacks and in some cases buildings must be surveyed onto the lot. The City sessives the right to request an improvisus area survey at any time prior to issuance of Certificate of Cocupancy. Building height survey Phone:	☐ Full Size drawings required. IDDESSEVER FREQUIREVENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream maintole rir Video tape of existing sewer required (see standard of	Other: cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Editals) Disconnect permit required. Reconnect permit required. el line you will need to schedule three (3) days in advance with the City of (6) 273-7800.			
spection. A property survey may be required to verify setbacks and in some cases buildings must be surveyed onto the lot. The City sessives the right to request an improvisus area survey at any time prior to issuance of Certificate of Cocupancy. Building height survey Phone:	☐ Full Size drawings required. IDDESSEVER FREQUIREVENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream maintole rir Video tape of existing sewer required (see standard of	Other: cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Editals) Disconnect permit required. Reconnect permit required. el line you will need to schedule three (3) days in advance with the City of (6) 273-7800.			
spection. A property survey may be required to verify sebados and in some cases buildings must be surveyed onto the lot. The City sessives the right to request an improvious area survey at any time prior to issuance of Certificate of Cocupancy. Building height survey	☐ Full Size drawings required. IDDES SEWER FREQUIREWINES Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rir Video tape of essiting sewer required (see standard of	Other: cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Editals) Disconnect permit required. Reconnect permit required. el line you will need to schedule three (3) days in advance with the City of (6) 273-7800.			
spection. A property survey may be required to verify setbacks and in some cases buildings must be surveyed onto the lot. The City sessives the right to request an improvisus area survey at any time prior to issuance of Certificate of Cocupancy. Building height survey Phone:	☐ If all Size drawings required. IDE SEWER REQUIREMENTS: Side sever requires a backflow preventer when connolower than the elevation of the upstream manhole rire. Video tape of existing sever required (see standard.) New connection. ☐ connect to existing. Other: Note: When side sever is to be connected to the lake. Mercer Island Maintenance Department of 20 DPROVED CODE ALTERNATIVES: Code alternatives must be inspected. Refer to the inspectio CA1:	other: Other: Other:			
Surveyor: Bullding height survey Phone: Phone: Phone: Bullding height survey Bullding height survey Phone: Phone: Bullding setback survey Impervious surface survey Impervious s	☐ Full Size drawings required. IDDE SEWER REQUIREVENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rir Video tape of sixthis sewer require (see standard of lower connection. ☐ Connect to easting. Other When side sewer is to be connected to the law More: When side sewer is to be connected to the law More: When the sewer is to be connected to the law decree Island Maintenance Department at (20 Connected Side Side Side Side Side Side Side Si	Other: cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Editable Disconnect permit required. Reconnect permit required. Reconnect permit required. le line you will need to schedule three (3) days in advance with the City of 16) 273-7800. In Checklist CA2: In Checklist Application shall be submitted when checked):			
Surveyor: Building height survey Building setback survey Building setback survey Building setback survey Building setback survey District Other: A Building inspection prior to demolition is required for all legally pocconforming single family dwelling to ensure no more than 40 piercent of the dwelling secretor valls are structurally altered. Contact the Building Inspector at (266) 275-7730. District District Owl (Potalling Refining and foundation work withing seologic hazard areas is NOT PERMITED between October 1 and April 1 thinbut an approved Sessonal Development Limitation Walver. Geotechnical Report provided. All construction must comply with the recommendations of the Geotechnical Report, A copy of report and other predetential information must be epton site at all times. Geotechnical Report provided. All construction must comply with the recommendations of the Geotechnical Report, A copy of report and other predetential information must be epton site at all times. Geotechnical Report provided. All construction must comply with the recommendations of the Geotechnical Report, A copy of report and other predetential information must be epton site at all times. Geotechnical Report provided. All construction must comply with the recommendations of the Geotechnical Report, A copy of report and other provided. All construction must comply with the recommendation of the Geotechnical Report. A copy of report and other provided. All construction must comply with the recommendation of the Geotechnical Report provided. All construction must comply with the recommendation of the Geotechnical Report provided. All construction must comply with the recommendation of the Geotechnical Report provided. All construction must comply with the recommendation of the Geotechnical Report provided.	☐ If all Size drawings required. IDE SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rire. Video tape of swisting sewer require (see standard.) New connection. ☐ connect to existing. Other: Note: When side sewer is to be connected to the lake. Mercer Island Maintenance Department at (20. PPROVED CODE ALTERNATIVES: Ode alternatives must be Inspected. Refer to the Inspectio CA1: UNEVEY REQUIREMENTS THE Following spore unreyor shall verify points: chosen for height calculations a spacetion. A procedure surveyor shall verify points chosen for height calculations a spacetion. A procedure surveyor shall verify points chosen for height calculations	Other: cetting to the lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties. Edetails) Disconnect permit required. Reconnect permit required. elline you will need to schedule three (3) days in advance with the City of 6) 275-7800. n Checklist CA2: Information must be submitted when checked: Independent on the place of City foundation backs and in some cases buildings must be surveyed onto the lot. The City			
Bulding height survey Bulding height survey Bulding setback setback sequirements Bulding spector at (206) 275-7730. Bulding spector spector at (206) 275-7730. Bulding spector	☐ If all Size drawings required. IDE SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rire. Video tape of swisting sewer require (see standard.) New connection. ☐ connect to existing. Other: Note: When side sewer is to be connected to the lake. Mercer Island Maintenance Department at (20. PPROVED CODE ALTERNATIVES: Ode alternatives must be Inspected. Refer to the Inspectio CA1: UNEVEY REQUIREMENTS THE Following spore unreyor shall verify points: chosen for height calculations a spacetion. A procedure surveyor shall verify points chosen for height calculations a spacetion. A procedure surveyor shall verify points chosen for height calculations	other: cetting to the lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties. Edetails) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: In Checklist Ch			
Guiding setback survey Green Gre	☐ Full Size drawings required. Dipper SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole ring the sewer sequence (see standard or connect to easting.) Dipper Sewer Sewer is to be connected to the law Mercer Island Maintenance Department at (20 Mercer Island Maintenance Island Mercer Island Mercer Island Maintenance Island Mercer Island Mer	cetting to the lake line or when the elevation of the lowest plumbing fixture is m or when side sever is shared with one or more properties. Edetails) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA2: CA2: CA3:			
mpervious surface survey	☐ If all size drawings required. IDBE SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rir Video tape of existing sewer require (see standard of the province to existing.) Ownect to existing. Other was also sewer is to be connected to the law Mercer Island Maintenance Department at (20 OPPROVED CODE ALTERNATIVES: CA1: CA1: CA2: CA3: CA3	cetting to the lake line or when the elevation of the lowest plumbing fixture is m or when side sever is shared with one or more properties. Edetails) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA2: CA2: CA3:			
MAXIMUM 40 PERCENT ALTERATION INSPECTION: MCTRIANGEMENT A Building Inspection prior to demolition is required for all legally onconforming single family dwelling to ensure no more than 40 percent of the dwelling's exterior walls are structurally altered. Contact the Building Inspector at (206) 275-7730. ### DEFOTECHNICAL INFORMATION: and clearing, grading, filling and Soundation work within geologic hazard areas is NOT PERMITTED between October 1 and April 1 inthout an approved Seasonal Development Limitation Waiver. Geotechnical Report provided. All construction must comply with the recommendations of the Geotechnical Report. A copy of report and other geotechnical information must be kept on site at all times. Geotechnical Emport provided. All construction must comply with the recommendations of the Geotechnical Report. A copy of report and other geotechnical information must be kept on site at all times. Geotechnical Emport provided. All construction must be sept on site at all times. Geotechnical and area Grading not permitted between October 1 through April 1. Applies (Geologic Hazard area). Grading not permitted between October 1 through April 1. Waiver approved. Grading and exavation permitted subject to all conditions noted in Seasonal Development Limitation Waiver Permit.	□ full size drawings required. □ SI size star specification of the upstream manhole rich developed that the elevation of the upstream manhole rich developed sexing sewer requires a backflow preventer when connolower than the elevation of the upstream manhole rich developed sexing sewer requires (sex standard on his connect to existing. □ Other: □ Note: When side sewer is to be connected to the lake Mercer Island Maintenance Department at 20 DPROVED CODE ALTERNATIVES: 0 de alternatives must be inspected. Refer to the inspectio □ CA1: □ CA1: □ CA2: □ CA3: □ CA3: □ CA3: □ CA4:	cetting to the lake line or when the elevation of the lowest plumbing fixture is m or when side sever is shared with one or more properties. Edetails) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA2: CA2: CA3:			
MAMIMUM 40 PERCENT ALTERATION INSPECTION: INTERMEMBER A Bulding inspection prior to demolition is required for all legally onconforming single family dwelling to ensure no more than 40 percent of the dwelling's exterior walls are structurally altered. Contact the building inspector at (206) 275-7730. □ Vid / Oralnage □ LUP / Setback requirements FEOTECHNICAL INFORMATION: General Filling and foundation work within geologic hazard areas is NOT PERMITTED between October 1 and April 1 inhout an approved Seasonal Development Limitation Waiver. General Filling and Foundation work within geologic hazard areas is NOT PERMITTED between October 1 and April 1 inhout an approved Seasonal Development Limitation Waiver. General Filling and Foundation work where the properties of the Geotechnical Report, A copy of report and other geotechnical Information must be kept on site at all times. General Filling All Filli	□ full size drawings required. □ SI size star specification of the upstream manhole rich developed that the elevation of the upstream manhole rich developed sexing sewer requires a backflow preventer when connolower than the elevation of the upstream manhole rich developed sexing sewer requires (sex standard on his connect to existing. □ Other: □ Note: When side sewer is to be connected to the lake Mercer Island Maintenance Department at 20 DPROVED CODE ALTERNATIVES: 0 de alternatives must be inspected. Refer to the inspectio □ CA1: □ CA1: □ CA2: □ CA3: □ CA3: □ CA3: □ CA4:	cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sever is shared with one or more properties. Edetails) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA2: CA2: CA3: C			
A Bullding Inspection prior to demolition is required for all legally nonconforming single family dewling to ensure no more than 40 percent of the dwelling's exterior valls are structurally attend. Contact the Building Inspector at (206) 275-7730. Civil / Oranage	□ Full Size drawings required. □ Survey REQUIREMENTS: □ Side sever requires a backflow preventer when connolower than the elevation of the upstream manhole rire. □ Video tape of existing sewer require (see standard.) □ New connection. □ connect to existing. □ Other: □ Note: When side sewer is to be connected to the lake. ■ Mercer Island Maintenance Department at (2) ■ CAPROVED CODE ALTERNATIVES: □ CAR:	cetting to the lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties. Edetails) Disconnect permit required. Reconnect permit required. elline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA2: CA3:			
40 percent of the dwelling's exterior walls are structurally altered. Contact the Building Inspector at (206) 275-7730. Civil / Oraninage	☐ In Use drawings required. IDEC SELVER REQUIREMENTS: Sele sever requires a backflow preventer when connolower than the elevation of the upstream manhole rire. Video tape of existing sewer required (see standard.) □ New connection. □ Connect to existing. □ Other: ■ Note: When side sever is to be connected to the lake Wester bland Maintenance Department at COMPROVED CODE ALTERNATIVES: CAL: □ CAL: □ CAL: ■ CA	other: cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Editals) Disconnect permit required. Reconnect permit required. el line you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA2: On Open the original permit required of the properties of			
CWI / Oranage	□ Full Size drawings required. □ Full Size drawings required. □ Side sewer requires a backflow preventer when conn □ □ □ □ □ □ □ □ □	cetting to the lake line or when the elevation of the lowest plumbing fixture is me or when side sewer is shared with one or more properties. Extension Disconnect permit required. Bisconnect permit required. Bisconnect permit required. Bisconnect permit required. Color of the connect permit required and the connect permit required. Color of the connect permit required. Color of the connect permit required and color of the color of			
Accepted to the Control of the Contr	☐ If all Size drawings required. IDEESEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rir Video tape of existing sewer required (see standard Video tape of existing sewer required (see standard Video tape of existing sewer required (see standard Video tape of existing sewer load of the lake Weter Usland Maintenance Department at COPPROVED CODE ALTERNATIVES: CA1: URIVEY REQUIREMENTS THE INSECTION OF THE	Other:			
A paproved Seasonal Development Limitation Waiver. Geotechnical Report provided. All construction must comply with the recommendations of the Geotechnical Report. A copy of report and other geotechnical information must be kept on site at all times. Generative Impairer SEASONAL DEVELOPMENT LIMITATION RESTRICTION: □ Applies (Geologic Hazard area), Grading not permitted between October 1 through April 1. □ Waiver approved, Grading and excavation permitted subject to all conditions noted in Seasonal Development Limitation Waiver Permit.	☐ In Use drawings required. IDEC SELVER REQUIREMENTS: See sever requires a backflow preventer when connolower than the elevation of the upstream manhole rire. In the connection of the public department of the department of the develling section visits are the public department of the develling section visits are the public department of the develling section visits are the public department of the develling section visits are the public department of the develling section visits are the public department of the develling section visits are the public department of the develling section visits are the public department of the develling section visits are the public department of the pu	Other:			
A paproved Seasonal Development Limitation Waiver. Geotechnical Beport provided. All construction must comply with the recommendations of the Geotechnical Report. A copy of report and other geotechnical information must be kept on site at all times. Geotechnical Export Provided Fraction Comply with the recommendations of the Geotechnical Report. A copy of report and other geotechnical Information must be kept on site at all times. Finder	☐ If all Size drawings required. IDEESEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rir Video tape of existing sewer required (see standard Video tape of existing sewer required (see standard Video tape of existing sewer required (see standard Video tape of existing sewer load of the lake Weter Usland Maintenance Department at COPPROVED CODE ALTERNATIVES: CA1: URIVEY REQUIREMENTS THE INSECTION OF THE	Other:			
□ Geotechnical Report provided. All construction must comply with the recommendations of the Geotechnical Report. A copy of report and other geotechnical Information must be kept on site at all times. Phone	☐ If all size drawings required. IDEC SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rir Video tape of existing sewer required (see standard of the prevention of the developed section of the developed section of the prevention of the developed section o	cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Extension of the lowest plumbing fixture is more when side sewer is shared with one or more properties. Extension of the lowest plumbing fixture is more properties. The lowest plumbing is described in the lowest plumbing in the lowest plumbing is described in the lowest plumbing is described in the lowest plumbing is described in the lowest plumbing in the lowest plumbing is described in the lowest plumbing in lowest plumbing in the lowest plumb			
report and other geotechnical information must be kept on site at all times. Geotechnical Engineer SEASONAL DEVEMENT LIMITATION RESTRICTION: Applies (Geologic Hazard area). Grading not permitted between October 1 through April 1. Waiver approved, Grading and exavation permitted subject to all conditions noted in Seasonal Development Limitation Waiver Permit.	☐ If all Size drawings required. DIDE SEWER REQUIREMENTS: Side sewer requires a backflow preventer when connower than the elevation of the upstream manhole rivideo tape of existing sewer requires (see standard.) New connection.	certing to the lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties. Estatis) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA2: CA2: CA2: CA3: CA			
Geotechnical Engineer SEASONAL DEVELOPMENT LIMITATION RESTRICTION: Applies (Seologic Hazard area). Grading not permitted between October 1 through April 1. Walver approved. Grading and exavation permitted subject to all conditions noted in Seasonal Development Limitation Waiver Permit.	☐ If all size drawings required. IDEC SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rir Video tape of existing sewer require (see standard of the prevention of the prevention of the prevention of the prevention of the upstream manhole rir Video tape of existing sewer required (see standard with the prevention of the develor of the prevention of the prevention of the develor of the prevention of the prevention of the develor of the prevention of the prevention of the develor of the prevention of the prevention of the develor of the prevention of the prevention of the develor of the prevention of the prevention of the develor of the prevention	cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Extension of the lowest plumbing fixture is more when side sewer is shared with one or more properties. Extension of the lowest plumbing fixture is more properties. The lowest plumbing is shared with the city of lowest plumbing in the lowest plumbing in disparation of the lowest plumbing in disparation of the lowest plumbing in lowest plumbing in the lowest plumb			
SEASONAL DEVELOPMENT LIMITATION RESTRICTION: Applies (Geologic Hazard area). Grading not permitted between October 1 through April 1. Waiver approved. Grading and excavation permitted subject to all conditions noted in Seasonal Development Limitation Waiver Permit.	□ full Size drawings required. IDDE SEWER REQUIREMENTS: Side sever requires a backflow preventer when connolower than the elevation of the upstream manhole rity Video tape of existing sever required (see standard.) Nets connection. □ connect to existing. Other: Note: When side sever is to be connected to the lake Mercer Island Maintenance Department at 20 and the Connect of the lake Mercer Island Maintenance Department at 20 and the Connect of the Island Maintenance Department at 20 and the Island Maintenance Department at 20 and Parker Island Maintenance Department at 20 approved to CA1: □ CA1: □ CA1: □ CA1: □ CA1: □ CA1: □ Surveyor: □ Building height survey. □ Unique Setbock survey. □ Unique Setbock survey. □ Unique Setbock survey. □ Unique Setbock survey. □ MAINMUM 40 PERCENT ALTERATION INSPECTION: A Building height survey. □ CA Building setbock survey. □ CA Building height survey. □ CA Buildin	certing to the lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties. Estetisi) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA2: CA2: CA3: C			
SEASONAL DEVELOPMENT LIMITATION RESTRICTION: Applies (Geologic Hazard area). Grading not permitted between October 1 through April 1. Waiver approved. Grading and excavation permitted subject to all conditions noted in Seasonal Development Limitation Waiver Permit.	□ full Size drawings required. IDEG SEWER REQUIREMENTS: Side sever requires a backflow preventer when connolwer than the elevation of the upstream manhole rity video tape of existing sewer require (see standard.) Nets connection. □ connect to existing. Other: Note: When side sewer is to be connected to the lake Meterer Island Maintenance Department at 20 and the connection of the lake Meterer Island Maintenance Department at 20 and the lake Meterer Island Maintenance Department at 20 and the lake Meter Island Maintenance Department at 20 and the lake Meter Island Maintenance Department at 20 and the lake Meter Island Maintenance Department at 20 appearance Island Island Maintenance Department at 20 appearance Island Maintenance Department at 20 appearance Island Maintenance Island Mainten	certing to the lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties. Estetisi) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA2: CA2: CA3: C			
☐ Applies (Geologic Hazard area). Grading not permitted between October 1 through April 1. ☐ Walver approved. Grading and excavation permitted subject to all conditions noted in Seasonal Development Limitation Walver Permit.	□ full Size drawings required. □ SIDE SEWER REQUIREMENTS: □ Side sewer requires a backflow preventer when connolwer than the elevation of the upstream manhole rity Video tape of existing sewer require (see standard.) □ New connection. □ connect to existing. □ Other: □ Note: When side sewer is to be connected to the lake Mercer Island Maintenance Department at COMPONED CODE ALTERNATIVES: □ CAI: □ CAI: □ CAI: □ CAI: □ SIDE SEMENT STANDARD SEMENT	certing to the lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties. Estatis) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA			
☐ Walver approved. Grading and excavation permitted subject to all conditions noted in Seasonal Development Limitation Walver Permit. ———————————————————————————————————	□ Full Size drawings required. IDEC SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rir Video tape of existing sewer require (see standard in the prevention of the prevention of the sewer is to be connected to the kind when the sewer is to be connected to the kind where is island Maintenance Department at (20 PPROVED CODE ALTERNATIVES: CA1: SURVEY REQUIREMENTS must be inspected. Refer to the Inspection of the inspecti	certing to the lake line or when the elevation of the lowest plumbing fixture is m or when side sewer is shared with one or more properties. Estatis) Disconnect permit required. Reconnect permit required. eline you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: CA			
Limitation Waiver Permit.	Full Size drawings required. DIPC SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rin Video tape of existing sewer required (see standard or video tape of existing sewer required (see standard or video tape of existing sewer required (see standard or video tape of existing sewer is to be connected to the law of the provided of the provided or video tape o	cetting to the lake line or when the elevation of the lowest plumbing fixture is me or when side sewer is shared with one or more properties. Extension Disconnect permit required. Reconnect permit required. Reconnect permit required. State Reconnect permit required. Reconnect permit required. Ca2:			
	Full Size drawings required. DIED SEVER REQUIREMENTS: Side sever requires a backflow preventer when conn lower than the elevation of the upstream manhole rir Video tape of existing sewer require (see standard.) Nete connection.	cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Exhaustically Disconnect permit required. Bisconnect permit required. Case line you will need to schedule three (3) days in advance with the City of (6) 275-7800. Checklist CA2: CA2: CA2: CA3: CA4: CA5: CA5: CA5: CA6: CA7: CA6: CA7: CA7: CA8: CA8: CA8: CA8: CA8: CA9: CA8: CA9:			
Permit number Approved by Date	Full Size drawings required. DiPC SEWER REQUIREMENTS: Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rin Video tape of existing sewer require (see standard of the provided of the	cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Exhaustically Disconnect permit required. Bisconnect permit required. Case line you will need to schedule three (3) days in advance with the City of (6) 275-7800. Checklist CA2: CA2: CA2: CA3: CA4: CA5: CA5: CA5: CA6: CA7: CA6: CA7: CA7: CA8: CA8: CA8: CA8: CA8: CA9: CA8: CA9:			
Permit number Approved by Date	Full Size drawings required. Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manifole ric Video tape of existing sewer require (see standard of the connect to existing.) Wheter the prevention Connect to existing. On the connect to the last of the connect to t	cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sewer is shared with one or more properties. Exhaustically Disconnect permit required. Bisconnect permit required. Case line you will need to schedule three (3) days in advance with the City of (6) 275-7800. Checklist CA2: CA2: CA2: CA3: CA4: CA5: CA5: CA5: CA6: CA7: CA6: CA7: CA7: CA8: CA8: CA8: CA8: CA8: CA9: CA8: CA9:			
	Full Size drawings required. Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rich the sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rich the sewer is to be connected to the law connection. Connect to easting. Note: When side sewer is to be connected to the law Mercer Island Maintenance Department at (20 Mercer Island Maintenance Island Mercer Island Maintenance Island	cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sever is shared with one or more properties. Extension of the side sever is shared with one or more properties. Extension Disconnect permit required. Reconnect permit required. Disconnect permit required. Reconnect permit required. Reconnect permit required.			
	Full Size drawings required. Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rich the sewer requires a backflow preventer when conn lower than the elevation of the upstream manhole rich the sewer is to be connected to the law connection. Connect to easting. Note: When side sewer is to be connected to the law Mercer Island Maintenance Department at (20 Mercer Island Maintenance Island Mercer Island Maintenance Island	cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sever is shared with one or more properties. Extension of the side sever is shared with one or more properties. Extension Disconnect permit required. Reconnect permit required. Disconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit required. Reconnect permit requirements.			
	Full Size drawings required. Side sewer requires a backflow preventer when conn lower than the elevation of the upstream manifole ric Video tape of easiting sewer require (see standard Video tape of easiting sewer require (see standard New Connection Connect to easiting. Note: When side sewer is to be connected to the lab. Note: When side sewer is to be connected to the lab. Note: When side sewer is to be connected to the lab. Note: When side sewer is to be connected to the lab. Note: When side sewer is to be connected to the lab. Note: When side sewer is to be connected to the lab. Note: When side sewer is to be connected to the lab. Note: When side sewer is to be connected to the lab. Note: When side sewer is to the lab. Note: Note	cetting to the lake line or when the elevation of the lowest plumbing fixture is mor when side sever is shared with one or more properties. Extension Disconnect permit required. Bisconnect permit required. Case line you will need to schedule three (3) days in advance with the City of (6) 275-7800. In Checklist CA2: In Checklist CA2: In Checklist CA2: In Checklist Phone: Phone: Phone: In Checklist In Case when the submitted at the time of City foundation backs and in some cases buildings must be surveyed onto the lot. The City any time prior to issuance of Certificate of Occupancy. Phone: In Checklist In Checklist In Checklist In Checklist In Checklist In Checklist In Case when the submitted at the time of City foundation backs and in some cases buildings must be surveyed onto the lot. The City any time prior to issuance of Certificate of Occupancy. In Checklist In Checklist In Checklist Phone: In Checklist In C			

O BE COMPLETED BY CPD	restoration complete and as-bull drawings ready for submittad. Tinal Inspection Bullding, including electrical / mechanical / plumbing. If applicable, provide closeout (summary) letters from Engineer, Special Inspectors, Seccienchical Engineer, and exterior wall, cladding Inspectors (EIFS). 90 DAY TEMPORARY CERTIFICATE OF OCCUPANCY (TCO):	APPROVED DRAWINGS MUST BE KEPT ON THE BUILDING SITE AT ALL TIMES DROIF	EVIEWED FOR CODE COMPLIANCE NAMI	PROJE ADDR
	Final Inspection. Tree Restoration	Ľ	E. GRIMA	DDRESS: 4008 90TH AVE
TO BE COMPLETED BY CPD	Connections to existing Sewer manholes		GRIMA - FAHRER RESIDENCE	OTH AVE SE
	reports of inspections Jolle and shoring installation, etc.)	CERTIFICATE OF OCC	issued after all required hispections have been performed and approved.	уркомед Аркомед
TO BE COMPLETED BY CPI	It is the applicant's responsibility to contact DSG to schedule ALL inspections appropriate for the project. Request inspections online at www.MybuddingPermit.com or by calling the inspection Holine at (206) 275-7730. Allow at least 24 hours (48 hours for Reinforcing steel) in advance of estated inspection. Be specific as to type of inspection. Inspector shall initial and date appropriate inspection only if approved. Note: *Rems marked with an "*" require a separate permit. It is the applicants responsibility to apply for and obtain all City of Mercer Island permits. INSPECTIONS: Unand noted or fiscal inspection. Projects Date ** Approved** Presconstruction Meeting to Review Conditions of Permit Approval. Tree protection. Tree protection. Sewer disconnect and cap. If applicable, separate side-sewer permit required. Sewer disconnect and cap. If applicable, separate side-sewer permit required. Sewer disconnect and cap. If applicable, separate side-sewer permit required. Inspection of the property in the property t	JPANCY	J.	PERMIT NUMBER Dote Dote