

XQ60 STANDARD EQUIPMENT

CAT C3.4B DIESEL ENGINE

Heavy-duty.

After treatment.

GENERATOR

1514P frame.

CONTROL PANEL

Digital EMCP4.2B set mounted controller.

CAT CONNECT REMOTE MONITORING

Provides package monitoring and management.

COOLING SYSTEM

Package mounted radiator with vertical air discharge.

Filled from factory.

CHARGING / STARTING SYSTEM

12V heavy duty starting motor and charging alternator c/w battery isolator.

FUEL SYSTEM

24hr dual wall fuel tank with 3 way directional valve for external supply.

AIR FILTER

Cyclonic/paper with dust cup and service indicator.

DISTRIBUTION

Single, robust enclosure for controls and distribution c/w 4 pole circuit breaker and safety cut off.

STRUCTURE

Heavy Duty steel base frame with integral fuel tank.

Lifting frame and 4 point lift.

Base frame is wider than enclosure to protect generator set during transportation.

ENCLOSURE

Sound attenuating, galvanised steel enclosure with exceptional noise reduction performance.

EXHAUST

Integrated spark arresting silencer.

LUBE OIL

On engine primary and secondary oil filters. Filled from factory.

GENERAL

Factory tested and inspected.

